# Safety Data Sheet according to Regulation (EC) 'No. 2020/878



## SECTION 1: Identification of the Substance/Mixture and of the Company/Undertaking

1.1 Product Identifier IS560-433B Revision Date: 26/12/2023

Product Name: STONLUX SL PART B Supersedes Date: 28/12/2021

UFI Code: No Information

Contain nanoform:

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Component of multicomponent industrial coatings - Industrial use. Advised against:

others than recommended

1.3 Details of the supplier of the safety data sheet

Importer: None

Manufacturer: StonCor Middle East L.L.C.

Plot # B518, Al Quoz Industrial Area 3

P.O. Box: 3034 Dubai, U.A.E.

Regulatory / Technical Information:

+971 4 347 0460 +971 4 347 0242 (fax)

Datasheet Produced by: Rivero, Melody - ehs@stoncor.com

1.4 Emergency telephone number: CHEMTREC +1 703 5273887 (Outside US)

112 (24/7)

Croatia +3851 2348 342 (24/7 in Croatian and English)

Iceland 112 (24/7) Malta 112 (24/7)

## **SECTION 2: Hazards Identification**

## 2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

#### **HAZARD STATEMENTS**

Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Eye Irritation, category 2	H319
Acute Toxicity, Inhalation, category 4	H332
Carcinogenicity, category 1A	H350-1A
STOT, single exposure, category 1	H370
Hazardous to the aquatic environment, Chronic, category 2	H411

## 2.2 Label elements

## Symbol(s) of Product







## Signal Word

Danger

#### Named Chemicals on Label

Benzyl alcohol, quartz (silicon dioxide), Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700), Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

## **HAZARD STATEMENTS**

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
STOT, single exposure, category 1	H370	Causes damage to organs.
Hazardous to the aquatic environment,	H411	Toxic to aquatic life with long lasting effects.
Chronic, category 2		

## PRECAUTION PHRASES

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash hands thoroughly after handling.
Avoid release to the environment.
Wear protective gloves/protective clothing/eye protection/ face protection.
Wear respiratory protection.
IF ON SKIN: Wash with plenty of soap and water.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
IF exposed, call a POISON CENTER or doctor/physician.
IF exposed or concerned: Get medical advice/attention. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Collect spillage.

#### 2.3 Other hazards

No Information

## Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

**Endocrine disrupting properties - Toxicity** 

Name According to EEC CAS-No.

No Information

**Endocrine disrupting properties - Ecotoxicity** 

Name According to EEC CAS-No.

No Information

## **SECTION 3: Composition/Information On Ingredients**

## 3.1 Substances

Not applicable

## 3.2 Mixtures

## Hazardous ingredients

Name According to EEC EINEC No. CAS-No.	<u>%</u>	<u>Classifications</u>	SCL Value: ATE Value:	
REACH Reg No.			•	M-Factor:
quartz (silicon dioxide) 238-878-4	25 - <50	H350-370	SCL Value:	-
14808-60-7 No Information		Carc. 1A, STOT SE 1	ATE Value:	-
			M-Factor: (acute)	-
			M-Factor: (chronic)	-

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) 500-033-5 25068-38-6 01-2119456619-26-0029	25 - <50	H315-317-319-411  Aquatic Chronic 2, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1	SCL Value:  ATE Value:  M-Factor: (acute)	-
			M-Factor: (chronic)	-
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 271-846-8	2.5 - <10	H315-317	SCL Value:	-
68609-97-2		Skin Irrit. 2, Skin Sens. 1	ATE Value:	-
No Information	Skin Irrit. 2, Skin Sens. 1		M-Factor: (acute)	-
			M-Factor: (chronic)	-
Benzyl alcohol 202-859-9	1.0 - <2.5	H302-312-319-332	SCL Value:	-
100-51-6			ATE Value:	-
No Information		Acute Tox. 4 Dermal, Acute Tox. 4 Inhalation, Acute Tox. 4 Oral, Eye Irrit. 2	M-Factor: (acute)	-
			M-Factor: (chronic)	-

titanium dioxide 236-675-5	1.0 - <2.5	H351	SCL Value:	-
13463-67-7			ATE Value:	-
No Information		Carc. 2		
			M-Factor: (acute)	-
			M-Factor: (chronic)	-
p-Menth-1-en-8-ol	<0.1	H315-319	SCL Value:	-
98-55-5 No Information		Eye Irrit. 2, Skin Irrit. 2	ATE Value:	-
			M-Factor: (acute)	-
			M-Factor: (chronic)	-

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

## **SECTION 4: First-aid Measures**

## 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person.

## Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

## 4.2 Most important symptoms and effects, both acute and delayed

No Information

## 4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention is required. No information available on clinical testing and medical monitoring. Specific

toxicological information on substances, if available, can be found in section 11.

## **SECTION 5: Firefighting Measures**

## 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

## 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Water sprayDry powderAlcohol-resistant foamCarbon dioxide (CO2). Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

## **SECTION 6: Accidental Release Measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

## 6.1.2 For emergency responders

See Section 7, 8 and 10 for further information.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

## 6.4 Reference to other sections

**FURTHER INSTRUCTIONS:** Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

## **SECTION 7: Handling and Storage**

#### 7.1 Precautions for safe handling

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

## 7.3 Specific end use(s)

No specific advice for end use available.

## **SECTION 8: Exposure Controls/Personal Protection**

## 8.1 Control parameters

# Ingredients with Occupational Exposure Limits

Name	CAS-No.	LTEL ppm	STEL ppm	STEL mg/m3	LTEL mg/m3
quartz (silicon dioxide)	14808-60-7				
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6				
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	68609-97-2				
Benzyl alcohol	100-51-6				
titanium dioxide	13463-67-7				
p-Menth-1-en-8-ol	98-55-5				

Name CAS-No. OEL Note

25068-38-6

quartz (silicon dioxide) 14808-60-7

Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Oxirane, mono[(C12-14-alkyloxy)methyl] 68609-97-2

derivs.

Benzyl alcohol 100-51-6

titanium dioxide 13463-67-7

p-Menth-1-en-8-ol 98-55-5

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

#### **Chemical Name:**

EC No.: CAS-No.:

## **DNELs - Derived no effect level**

	Workers				Consumers			
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							
Inhalation								
Dermal								

#### PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

#### 8.2 Exposure controls

**Personal Protection** 

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Rubber or plastic apron.

**OTHER PROTECTIVE EQUIPMENT:** No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

## **SECTION 9: Physical and Chemical Properties**

#### 9.1 Information on basic physical and chemical properties

Colour: Viscous Liquid

**Physical State** Liquid Odor Ероху

Odor threshold Not determined Hq Not determined Melting point / freezing point (°C) Not determined

Boiling point or initial boiling point and

boiling range (°C)

80 - N.D.

Not determined

Flash Point, (°C) 100

**Evaporation rate** Slower Than Ether

Flammability (solid, gas) Not determined

Llower and upper explosive limit Not determined

Vapour Pressure Not determined Relative vapour density Heavier Than Air Density and/or relative density Not determined Solubility in / Miscibility with water Not determined

Partition coefficient: n-octanol/water Not determined Auto-ignition temperature (°C) Not determined Decomposition temperature (°C)

Kinematic viscosity Unknown

Particle characteristics Not applicable to liquids

#### 9.2 Other information

VOC Content g/l: 0

Specific Gravity (g/cm3) 1.577

## **SECTION 10: Stability and Reactivity**

## 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

## 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

Direct sources of heat.

#### 10.5 Incompatible materials

Strong oxidizing agents.

#### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as definied in Regulation (EC) No 1272/2008

**Acute Toxicity:** 

Oral LD50: No information available.

Inhalation LC50: No information available.

Dermal LD50: No Information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

**Toxicity for reproduction:** No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

**Aspiration hazard:** No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CA	S-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
25	5068-38-6	Reaction product: bisphenol- A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	>2000 mg/kg, rat, oral	>2000 mg/kg, rat		0.000	0.000

17100 mg/kg, Oxirane, mono[(C12-14-68609-97-2 0.000 0.000 alkyloxy)methyl] derivs. oral, rat 2000 mg/kg, 100-51-6 Benzyl alcohol 1230 mg/kg, rat 1000 ppm, rat 0.000 0.000 rabbit 10000 mg/m3, 13463-67-7 titanium dioxide 0.000 0.000 oral (rat)

#### Additional Information:

No Information

## 11.2 Information on other hazards

**Endocrine disrupting properties - Toxicity** 

Name According to EEC CAS-No.

No Information

## **SECTION 12: Ecological Information**

## 12.1 Toxicity:

EC50 48hr (Daphnia):No informationIC50 72hr (Algae):No informationLC50 96hr (fish):No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

**12.4 Mobility in soil:** No information

12.5 Results of PBT and vPvB

assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

## 12.6 Endocrine disrupting properties

**Endocrine disrupting properties - Ecotoxicity** 

Name According to EEC CAS-No.

No Information

#### **12.7 Other adverse effects:** No information

CAS-No.	Name According to EEC	EC50 48hr	IC50 72hr	LC50 96hr
14808-60-7	quartz (silicon dioxide)	No information	No information	
25068-38-6	Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	No information	No information	
68609-97-2	Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	No information	No information	

100-51-6 Benzyl alcohol 230 mg/l 700 mg/l 460 mg/l

>100 mg/l (EC50, 48h,

13463-67-7 titanium dioxide Daphnia magna No information >1000 mg/l

OECD202)ation

98-55-5 p-Menth-1-en-8-ol No information No information No information

## **SECTION 13: Disposal Considerations**

WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 080111
Packaging Waste Code: 150110

## **SECTION 14: Transport Information**

		ADR/RID	ADN	IMDG	IATA
14.1	UN-number or ID number	UN 3082	UN 3082	UN 3082	UN 3082
14.2	UN proper shipping name	Environmentally Hazardous Substance, Liquid, N.O.S.	Environmentally Hazardous Substance, Liquid, N.O.S.	Environmentally Hazardous Substance, Liquid, N.O.S.	Environmentally Hazardous Substance, Liquid, N.O.S.
14.3	Transport Hazard Class(es)	9	9	9	9
14.4	Packing Group	III	III	III	III
14.5	Enviromental Hazards	No Information	No Information	No Information	No Information

14.6 Special precautions for user Unknown

**EmS-No.:** F-A, S-F

14.7 Maritime transport in bulk according to IMO Unknown

intruments

## **SECTION 15: Regulatory Information**

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

**National Regulations:** 

Denmark Product Registration Number: Not available

Danish MAL Code: Not available

Danish MAL Code - Mixture: Not available

Sweden Product Registration Number: Not available

Norway Product Registration Number: Not available

Germany WGK Class: Not available

Covered by Directive 2012/18/EC (Seveso III): Not applicable

Restrictions to product or to substances according

to Annex XVII, Regulation (CE) 1907/2006: Not applicable

Annex XIV, Regulation (CE) 1907/2006 - Authorisation List:

CAS-No. Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List - Art. 59 REACH):

CAS-No. Name According to EEC

Not Applicable

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## SECTION 16: Other Information

#### Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H350 May cause cancer.

H351 Suspected of causing cancer. H370 Causes damage to organs.

H411 Toxic to aquatic life with long lasting effects.

#### Reasons for revision

Revision Description Changed Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

01 - Identification

02 - Hazard Identification

03 - Composition/Information On Ingredients
 08 - Exposure Controls/Personal Protection
 09 - Physical and Chemical Properties

11 - Toxicological Information14 - Transportation Information15 - Regulatory Information

Substance Hazard Threshold % Changed

Revision Statement(s) Changed

#### List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

## Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu m$ .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.