Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200



1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 8125P0/B Revision Date: 03/13/2024

Product Name: FLEX EPOXY RESIN Supersedes Date: 02/28/2024

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Base component of 2 components coating - Industrial use. Advised against: others than

recommended

1.3 Details of the supplier of the safety data sheet

Manufacturer: Stonhard, Division of StonCor Group, Inc.

1000 East Park Avenue Maple Shade, NJ 08052

+1 856 7797500 (US)

Datasheet Produced by: ehs@stonhard.com

1.4 Emergency telephone number: +1 703-741-5970 - North America

+1 800-424-9300

+55 11 4349 1359 - South America +52 55 8526 4930 - Central America

+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa

+65 3163 8374 - Asia, South Asia, And Oceania

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2 Eye Irritation, category 2A Skin Irritation, category 2 Skin Sensitizer, category 1 STOT, single exposure, category 3, RTI

2.2 Label elements

Symbol(s) of Product





Signal Word

Warning

Named Chemicals on Label

 $PHENOL,\,4,4'-(1-METHYLETHYLIDENE)\,BIS-,\,POLYMER\,WITH\,(CHLOROMETHYL)\,OXIRANE,\,polymer\,of\,epichlorohydrin\,-polyglycol$

HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/
	face protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a
	position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do so.
	Continue rinsing.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

No information

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous in	

Name According to EEC PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHYL) OXIRANE	EINEC No. 500-033-5	<u>CAS-No.</u> 25068-38-6	3-6 75-100 H315-317-319-335-4 A			
polymer of epichlorohydrin - polyglycol	607-873-2	26142-30-3	10 - <25	H315-317-319-412	Aquatic Chronic 3, Eye Irrit. 2, Skin Irrit. 2, Skin Sens. 1	

CAS-No. M-Factors

25068-38-6 26142-30-3

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. May cause sensitization by skin contact. Prolonged or repeated exposure increases the risk. Harmful to aquatic organisms.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Extremes of temperature and direct sunlight.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

<u>Name</u>	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling

PHENOL, 4,4'-(1- 25068-38-6

METHYLETHYLIDENE) BIS-,

POLYMER WITH (CHLOROMETHYL)

OXIRANE

polymer of epichlorohydrin -polyglycol 26142-30-3

Name CAS-No. OSHA PEL OSHA STEL

PHENOL, 4,4'-(1- 25068-38-6

METHYLETHYLIDENE) BIS-,

POLYMER WITH (CHLOROMETHYL)

OXIRANE

polymer of epichlorohydrin -polyglycol 26142-30-3

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.

EYE PROTECTION: Safety glasses.

HAND PROTECTION: Impervious gloves. Long sleeved clothing. Remove and wash contaminated clothing before re-use.

Rubber or plastic apron.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: yellow / amber

Physical State Liquid

Odor Faint epoxy

Odor threshold Not determined

pH Non-aqueous

Melting point / freezing point (°C)

Not determined

Boiling point/range (°C) N.D. - N.D.

Flash Point, (°F / °C) >201F / >94C

Evaporation rate Not determined

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive

limits

N.D - N.D.

 Vapour Pressure
 Not determined

 Vapour density
 Not determined

 Relative density
 Not determined

Solubility in / Miscibility with water Negligible

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Not determined

Not determined

Viscosity 1750 cps

Explosive properties Not applicable

Oxidising properties

Not applicable

9.2 Other information

VOC Content g/l:

Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

Specific Gravity (g/cm3) 1.146

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed. Stable. Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents. Acids and bases.

10.6 Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information Inhalation LC50: No information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
25068-38-6	PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHYL) OXIRANE	>2000 mg/kg, rat, oral	>2000 mg/kg, rat		0.000	0.000

Additional Information:

This product is classified as a "Reproductive Toxicity - Category 2" due to containing a substance classified as a reproductive toxin via ingestion / oral exposure route only. Normal product application methods by trained crew members would not present a risk of oral exposure or ingestion.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information
No information
No information

12.2 Persistence and degradability:No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB No information

assessment:

12.6 Other adverse effects: No information

CAS-No. LC50 96hr **Chemical Name** EC50 48hr IC50 72hr PHENOL, 4,4'-(1-METHYLETHYLIDENE) 25068-38-6 BIS-, POLYMER WITH (CHLOROMETHYL) 1.8 mg/l No information 1.3 mg/L **OXIRANE** 26142-30-3 polymer of epichlorohydrin -polyglycol No information No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number UN3082

14.2 UN proper shipping name Enivronmentally hazardous substance, liquid, n.o.s.

Technical name reaction product: bisphenol-a-(epichlorhydrin) epoxy resin

14.3 Transport hazard class(es) 9

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5 Environmental hazards Not applicable
14.6 Special precautions for user EmS-No.:
F-A, S-F

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

No SARA 313 substances exist in this product above de minimis concentrations.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category: Industrial Maintenance Coatings

EPA VOC Content Limit (g/l): 450
Product VOC Content (g/l) 12
Thinning Recommendations: None

Application Recommendations: For professional use only.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

California Proposition 65:

No Proposition 65 Chemicals exist in this product.

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

^{*} As per the federal EPA definition for coating categories in 40 CFR 59.401.

^{**} Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

Reasons for revision

No Information

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"

Half maximal inhibitory concentration

- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

IC50

CLP Classification, Labeling & Packaging Regulation ЕC European Commission European Union ΕU United States US CAS Chemical Abstract Service European Inventory of Existing Chemical Substances EINECS Registration, Evaluation, Authorization of Chemicals Regulation REACH Globally Harmonized System of Classification and Labeling of Chemicals GHS Long term exposure limit LTEL STEL Short term exposure limit Occupational exposure limit Parts per million ppm Milligrams per cubic meter mg/m3 Threshold Limit Value TLV ACGIH American Conference of Governmental Industrial Hygienists OSHA Occupational Safety & Health Administration PEL Permissible Exposure Limits VOC Volatile organic compounds Grams per liter g/l Milligrams per kilogram mg/kg Not applicable N/A Lethal dose at 50% LD50 LC50 Lethal concentration at 50% Half maximal effective concentration EC50

PBT Persistent bioaccumulative toxic chemical vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter \leq 10 μm .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.