# **Safety Data Sheet**

# Prepared in Accordance with HCS 29 C.F.R. 1910.1200



01/06/2023

# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 51252 Revision Date: 03/13/2024

Product Name: STONCHEM 140PRVG LT GRAY Supersedes Date:

RESIN

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Base component of 2 components coating - Industrial use. For use by appropriately trained applicators. Please see Technical Data Sheet. Advised against: others than

recommended

### 1.3 Details of the supplier of the safety data sheet

Manufacturer: Stonhard, Division of StonCor Group, Inc.

1000 East Park Avenue Maple Shade, NJ 08052

+1 856 7797500 (US)

Datasheet Produced by: ehs@stonhard.com

1.4 Emergency telephone number: +1 703-741-5970 - North America

+1 800-424-9300

+55 11 4349 1359 - South America +52 55 8526 4930 - Central America

+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa

+65 3163 8374 - Asia, South Asia, And Oceania

# 2. Hazard Identification

### 2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2 Carcinogenicity, category 1A Eye Irritation, category 2A Skin Irritation, category 2 Skin Sensitizer, category 1 STOT, single exposure, category 3, RTI

### 2.2 Label elements

### Symbol(s) of Product



### Signal Word

Danger

### Named Chemicals on Label

mica, quartz (silicon dioxide), PHENOL, 4,4'-(1-METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHYL) OXIRANE, alkyl glycidyl ether

### **HAZARD STATEMENTS**

| Skin Irritation, category 2                                  | H315    | Causes skin irritation.                          |
|--|---------|--|
| Skin Sensitizer, category 1                                  | H317    | May cause an allergic skin reaction.             |
| Eye Irritation, category 2A                                  | H319    | Causes serious eye irritation.                   |
| STOT, single exposure, category 3, RTI                       | H335    | May cause respiratory irritation.                |
| Carcinogenicity, category 1A                                 | H350-1A | May cause cancer.                                |
| Hazardous to the aquatic environment,<br>Chronic, category 2 | H411    | Toxic to aquatic life with long lasting effects. |

### PRECAUTION PHRASES

| P201                         | Obtain special instructions before use.   |
|------------------------------|---|
| P202                         | Do not handle until all safety precautions have been read and understood.   |
| P261                         | Avoid breathing dust/fume/gas/mist/vapours/spray.   |
| P273                         | Avoid release to the environment.   |
| P280                         | Wear protective gloves/protective clothing/eye protection/<br>face protection.  |
| P284                         | Wear respiratory protection.  |
| P302+352                     | IF ON SKIN: Wash with plenty of soap and water.   |
| P304+340                     | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  |
| P305+351+338                 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.       |
| P308+313<br>P333+313<br>P391 | IF exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Collect spillage. |

# 2.3 Other hazards

No Information

# Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# 3. Composition/Information On Ingredients

### 3.2 Mixtures

Hazardous ingredients

Name According to EEC EINEC No. CAS-No. % Classifications

| PHENOL, 4,4'-(1-<br>METHYLETHYLIDENE)<br>BIS-, POLYMER WITH<br>(CHLOROMETHYL)<br>OXIRANE | 500-033-5 | 25068-38-6  | 25 - <50   | H315-317-319-335-4<br>11 | Aquatic Chronic 2, Eye Irrit.<br>2, Skin Irrit. 2, Skin Sens. 1,<br>STOT SE 3 RTI  |
|--|-----------|-------------|------------|--------------------------|--|
| titanium dioxide   | 236-675-5 | 13463-67-7  | 10 - <25   | H351                     | Carc. 2  |
| mica   | 601-648-2 | 12001-26-2  | 2.5 - <10  | H319-335                 | Eye Irrit. 2, STOT SE 3 RTI  |
| alkyl glycidyl ether   | 601-719-8 | 120547-52-6 | 2.5 - <10  | H315-317                 | Skin Irrit. 2, Skin Sens. 1  |
| talc   |           | 14807-96-6  | 2.5 - <10  |                          |  |
| hydrated, amorphous silica   |           | 112926-00-8 | 1.0 - <2.5 |                          |  |
| 4-nonylphenol,<br>branched   | 284-325-5 | 84852-15-3  | 1.0 - <2.5 | H302-314-361-400-4<br>10 | Acute Tox. 4 Oral, Aquatic<br>Acute 1, Aquatic Chronic 1,<br>Repr. 2, Skin Corr. 1 |
| quartz (silicon dioxide)   | 238-878-4 | 14808-60-7  | 0.1 - <1.0 | H350-370                 | Carc. 1A, STOT SE 1  |

Product: 51252

CAS-No. M-Factors

25068-38-6 13463-67-7 12001-26-2 120547-52-6 14807-96-6 112926-00-8 84852-15-3 14808-60-7

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

# 4. First-aid Measures

Date Printed: 03/19/2024

#### 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

Irritating to skin. May cause sensitization by skin contact. Prolonged or repeated exposure increases the risk. Harmful to aquatic organisms.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

# 5. Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

### 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

# 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment.

#### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

# 7. Handling and Storage

# 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

# 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Extremes of temperature and direct sunlight.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### 7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

# 8. Exposure Controls/Personal Protection

# 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (US)

| <u>Name</u>   | CAS-No.   | ACGIH TWA                      | ACGIH STEL | ACGIH Ceiling |
|---|---|--------------------------------|------------|---------------|
| PHENOL, 4,4'-(1-<br>METHYLETHYLIDENE) BIS-,<br>POLYMER WITH (CHLOROMETHYI<br>OXIRANE  | 25068-38-6  |                                |            |               |
| titanium dioxide  | 13463-67-7  | 10 MGM3 10 MGM3                |            |               |
| mica  | 12001-26-2  | 3 MGM3                         |            |               |
| alkyl glycidyl ether  | 120547-52-6   |                                |            |               |
| talc  | 14807-96-6  | 2 MGM3                         |            |               |
| hydrated, amorphous silica  | 112926-00-8   | 10.00 MG/M3                    |            |               |
| 4-nonylphenol, branched   | 84852-15-3  |                                |            |               |
| quartz (silicon dioxide)  | 14808-60-7  | 0.025 MGM3                     |            |               |
|   |   |                                |            |               |
| <u>Name</u>   | CAS-No.   | OSHA PEL                       | OSHA STEL  |               |
| Name  PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHY) OXIRANE   | 25068-38-6  | OSHA PEL                       | OSHA STEL  |               |
| PHENOL, 4,4'-(1-<br>METHYLETHYLIDENE) BIS-,<br>POLYMER WITH (CHLOROMETHY)   | 25068-38-6  | OSHA PEL  15 MGM3              | OSHA STEL  |               |
| PHENOL, 4,4'-(1-<br>METHYLETHYLIDENE) BIS-,<br>POLYMER WITH (CHLOROMETHY)<br>OXIRANE  | 25068-38-6  |                                | OSHA STEL  |               |
| PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHY) OXIRANE titanium dioxide                                | 25068-38-6<br>_)<br>13463-67-7  | 15 MGM3                        | OSHA STEL  |               |
| PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHY) OXIRANE titanium dioxide mica                           | 25068-38-6<br>-)<br>13463-67-7<br>12001-26-2                              | 15 MGM3                        | OSHA STEL  |               |
| PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHY) OXIRANE titanium dioxide mica alkyl glycidyl ether      | 25068-38-6<br>-)<br>13463-67-7<br>12001-26-2<br>120547-52-6               | 15 MGM3<br>3 mg/m3             | OSHA STEL  |               |
| PHENOL, 4,4'-(1- METHYLETHYLIDENE) BIS-, POLYMER WITH (CHLOROMETHY) OXIRANE titanium dioxide mica alkyl glycidyl ether talc | 25068-38-6<br>-)<br>13463-67-7<br>12001-26-2<br>120547-52-6<br>14807-96-6 | 15 MGM3<br>3 mg/m3<br>0.1 MGM3 | OSHA STEL  |               |

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

### 8.2 Exposure controls

**Personal Protection** 

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.

**EYE PROTECTION:** Safety glasses.

HAND PROTECTION: Impervious gloves. Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas

# 9. Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance: gray resin

Physical State Liquid

Odor threshold EPOXY ODOR

Not determined

pH N/A

Melting point / freezing point (°C)

Boiling point/range (°C)

Flash Point, (°F / °C)

Evaporation rate

Not determined

Not determined

Not determined

Upper/lower flammability or explosive N/A - N/A

limits

Vapour Pressure N/A
Vapour density N/A

Relative density

Solubility in / Miscibility with water

Not determined
INSOLUBLE

Partition coefficient: n-octanol/water

Not determined

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity N/A

Explosive properties Not determined

Oxidising properties

Not determined

9.2 Other information

VOC Content g/l:

Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

Specific Gravity (g/cm3) 1.492

# 10. Stability and Reactivity

#### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

## 10.2 Chemical stability

No decomposition if stored and applied as directed. Stable. Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

### 10.4 Conditions to avoid

Extremes of temperature and direct sunlight.

#### 10.5 Incompatible materials

Strong oxidizing agents. Acids and bases.

# 10.6 Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

### 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: No information Inhalation LC50: No information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

**Toxicity for reproduction:** No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No.     | <u>Chemical Name</u>  | Oral LD50                  | Dermal LD50            | Vapor LC50 | Gas LC50 | Dust/Mist LC50        |
|-------------|---|----------------------------|------------------------|------------|----------|-----------------------|
| 25068-38-6  | PHENOL, 4,4'-(1-<br>METHYLETHYLIDENE) BIS-,<br>POLYMER WITH<br>(CHLOROMETHYL) OXIRANE | >2000 mg/kg,<br>rat, oral  | >2000 mg/kg,<br>rat    |            | 0.000    | 0.000                 |
| 13463-67-7  | titanium dioxide  | 10000 mg/kg,<br>oral (rat) |                        |            | 0.000    | 6,82 mg/l (rat)<br>4h |
| 12001-26-2  | mica  | >16000 mg/kg               |                        |            | 0.000    | 0.000                 |
| 120547-52-6 | alkyl glycidyl ether  |                            | >4500 mg/kg,<br>rabbit |            | 0.000    | 0.000                 |
| 84852-15-3  | 4-nonylphenol, branched   | 580 mg/kg oral<br>rat      | 2,031 mg/kg,<br>rabbit |            | 0.000    | 0.000                 |
| 14808-60-7  | quartz (silicon dioxide)  | >2000 mg/kg                |                        |            | 0.000    | 0.000                 |
|             |   |                            |                        |            |          |                       |

#### Additional Information:

This product is classified as a "Reproductive Toxicity - Category 2" due to containing a substance classified as a reproductive toxin via ingestion / oral exposure route only. Normal product application methods by trained crew members would not present a risk of oral exposure or ingestion. Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form or progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other silicates as impurities, and above dei minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems. This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

# 12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information
No information
No information

12.2 Persistence and degradability: No information

**12.3 Bioaccumulative potential:** No information

**12.4 Mobility in soil:** No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information

| CAS-No.     | Chemical Name   | EC50 48hr   | IC50 72hr      | LC50 96hr  |
|-------------|---|---|----------------|------------|
| 25068-38-6  | PHENOL, 4,4'-(1-METHYLETHYLIDENE)<br>BIS-, POLYMER WITH (CHLOROMETHYL)<br>OXIRANE | 1.8 mg/l  | No information | 1.3 mg/L   |
| 13463-67-7  | titanium dioxide  | >100 mg/l (EC50, 48h,<br>Daphnia magna<br>OECD202)ation | No information | >1000 mg/l |
| 12001-26-2  | mica  | No information  | No information |            |
| 120547-52-6 | alkyl glycidyl ether  | No information  | No information |            |
| 14807-96-6  | talc  | No information  | No information |            |
| 112926-00-8 | hydrated, amorphous silica  | No information  | No information |            |
| 84852-15-3  | 4-nonylphenol, branched   | .035 mg/L   | .0563 mg/L     | .1383 mg/l |
| 14808-60-7  | quartz (silicon dioxide)  | No information  | No information |            |

# 13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport Information

**14.1 UN number** UN3267

**14.2 UN proper shipping name** Environmentally Hazardous Substance, Liquid, N.O.S.

Technical name Not applicable

14.3 Transport hazard class(es) 9

Subsidiary shipping hazard Not applicable

14.4 Packing group PG III

14.5 Environmental hazards Not applicable
 14.6 Special precautions for user Not applicable
 EmS-No.: Not applicable

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

# 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

# U.S. Federal Regulations: As follows -

### **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

| <u>Chemical Name</u>    | CAS-No.    | <u>%</u> |
|-------------------------|------------|----------|
| 4-nonylphenol, branched | 84852-15-3 | 1.54     |
| n-butyl acetate         | 123-86-4   | 0.03     |
| Toluene                 | 108-88-3   | 0        |
| Ethylbenzene            | 100-41-4   | 0        |

# **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical NameCAS-No.dipropylene glycol methyl ether34590-94-8Naphthalene91-20-3

#### U.S. Clean Air Act:

EPA Coating Category: INDUSTRIAL MAINTENANCE COATINGS

EPA VOC Content Limit (g/l): 450
Product VOC Content (g/l) 5
Thinning Recommendations: None

Application Recommendations: FOR INDUSTRIAL USE ONLY

# U.S. State Regulations: As follows -

### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical NameCAS-No.trade secret - non-hazardousTS-73

# Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical NameCAS-No.trade secret - non-hazardousTS-73

#### California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov

WARNING: Reproductive Toxicant -- www.P65Warnings.ca.gov

# International Regulations: As follows -

#### \* Canadian DSL:

All chemical ingredients included on inventory or exempt.

# 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

# 16. Other Information

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

<sup>\*</sup> As per the federal EPA definition for coating categories in 40 CFR 59.401.

<sup>\*\*</sup> Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

H335 May cause respiratory irritation.

H350 May cause cancer.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

#### Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

02 - Hazard Identification

03 - Composition/Information On Ingredients

09 - Physical and Chemical Properties

11 - Toxicological Information14 - Transportation Information15 - Regulatory Information

Substance Chemical Name Changed Revision Statement(s) Changed

#### List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

### Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million
mg/m3 Milligrams per cubic meter
TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu m_{\star}$ 

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.