# **Safety Data Sheet**

# Prepared In Accordance With HCS 29 C.F.R. 1910.1200



# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 09313/A Revision Date: 05/29/2025

Product Name: STONCHEM 510 AMINE Supersedes Date: 06/18/2024

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Hardener for 2 components coatings - Industrial use. Advised against: others than

recommended

1.3 Details of the supplier of the safety data sheet

Manufacturer: Stonhard, Division of StonCor Group, Inc.

1000 East Park Avenue Maple Shade, NJ 08052

+1 856 7797500 (US)

Datasheet Produced by: ehs@stonhard.com

**1.4 Emergency telephone number:** +1 703-741-5970 - North America

+1 800-424-9300

+55 11 4349 1359 - South America +52 55 8526 4930 - Central America

+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, And Africa

+65 3163 8374 - Asia, South Asia, And Oceania

# 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 3
Hazardous to the aquatic environment, Chronic, category 2
Reproductive\_ToxicityF\_category\_1B
Skin Corrosion, category 1B
Skin Sensitizer, category 1

#### 2.2 Label elements

# Symbol(s) of Product



# Signal Word

Danger

## Named Chemicals on Label

4,4'-isopropylidenediphenol, Benzyl alcohol, Diethylenetriamine, N-(3-(trimethoxysilyl)propyl)ethylenediamine, 3-aminomethyl-3,5,5-trimethylcyclohexylamine, 4,4' - isopropylidenediphenol oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with dietheylenetriamine

## **HAZARD STATEMENTS**

Acute Toxicity, Oral, category 4	H302	Harmful if swallowed.
Skin Corrosion, category 1B	H314-1B	Causes severe skin burns and eye damage.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Acute Toxicity, Inhalation, category 3	H331	Toxic if inhaled.
Reproductive_ToxicityF_category_1B	H360F	May damage fertility.
Hazardous to the aquatic environment,	H411	Toxic to aquatic life with long lasting effects.
Chronic, category 2		

## PRECAUTION PHRASES

d
d
n/
or
g.
t in a
utes.
tion.
€.
II

#### 2.3 Other hazards

This product contains a component that is toxic by inhalation when aerosolized or sprayed. Please refer to section 11 of the SDS for toxicity information. Review the toxicity against the intended use. If product is not being aerosolized or sprayed, the inhalation toxicity may not be applicable.

This product is classified as a "Acute Toxicity, Inhalation, Category 1" due to containing Diethylenetriamine (CAS # 111-40-0). Numerous Industrial Hygiene air monitoring studies have been conducted by Stonhard to determine actual levels of exposure to Diethylenetriamine during product installations to application personnel. In each case levels of exposure were found to be well below the ACGIH Threshold Limit Value and NIOSH Recommended Exposure Limit of 1 ppm.

#### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# 3. Composition/Information On Ingredients

3.2 Mixtures					
Hazardous ingredients					
Name According to EEC Diethylenetriamine	EINEC No. 203-865-4	<u>CAS-No.</u> 111-40-0	<u>%</u> 25 - <50	<u>Classifications</u> H302-312-314-317-3 31	Acute Tox. 3 Inhalation, Acute Tox. 4 Dermal, Acute Tox. 4 Oral, Skin Corr. 1B, Skin Sens. 1
3-aminomethyl-3,5,5- trimethylcyclohexylamin e	220-666-8	2855-13-2	10 - <25	H302-314-317	Acute Tox. 4 Oral, Skin Corr. 1B, Skin Sens. 1A
4,4'- isopropylidenediphenol	201-245-8	80-05-7	10 - <25	H317-318-335-360F- 400-410	Aquatic Acute 1, Aquatic Chronic 1, Eye Dam. 1, Repr. 1B, Skin Sens. 1, STOT SE 3 RTI
4,4' - isopropylidenediphenol oligomeric reaction products with 1- chloro-2,3- epoxypropane, reaction products with dietheylenetriamine	500-072-8	31326-29-1	10 - <25	H302-312	Acute Tox. 4 Dermal, Acute Tox. 4 Oral
Benzyl alcohol	202-859-9	100-51-6	2.5 - <10	H302-312-317-319-3 31	Acute Tox. 3 Inhalation, Acute Tox. 4 Dermal, Acute Tox. 4 Oral, Eye Irrit. 2, Skin Sens. 1B
N-(3-(trimethoxysilyI) propyl)ethylenediamine	217-164-6	1760-24-3	2.5 - <10	H317-318-332-412	Acute Tox. 4 Inhalation, Aquatic Chronic 3, Eye Dam. 1, Skin Sens. 1

CAS-No. M-Factors

111-40-0 2855-13-2 80-05-7 31326-29-1 100-51-6 1760-24-3

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

## 4. First-aid Measures

#### 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

## Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

Causes severe burns. Harmful in contact with skin and if swallowed. Irritating to eyes and respiratory system.

## 4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention is required. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

# 5. Fire-fighting Measures

### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

#### 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

## Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

## 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

## 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

# 7. Handling and Storage

### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Do not breathe vapours or spray mist.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat,

drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### 7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

# 8. Exposure Controls/Personal Protection

# 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
Diethylenetriamine	111-40-0	1 PPM		
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2			
4,4'-isopropylidenediphenol	80-05-7			
4,4' - isopropylidenediphenol oligome reaction products with 1-chloro-2,3-epoxypropane, reaction products with dietheylenetriamine	0.020 20 .			
Benzyl alcohol	100-51-6			
N-(3-(trimethoxysilyl)propyl) ethylenediamine	1760-24-3			

Name	CAS-No.	OSHA PEL	OSHA STEL
Diethylenetriamine	111-40-0	4 MGM3, 1 PPM	
3-aminomethyl-3,5,5- trimethylcyclohexylamine	2855-13-2		
4,4'-isopropylidenediphenol	80-05-7		
4,4' - isopropylidenediphenol oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with dietheylenetriamine	31326-29-1		
Benzyl alcohol	100-51-6		
N-(3-(trimethoxysilyI)propyI) ethylenediamine	1760-24-3		

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

## 8.2 Exposure controls

Personal Protection

**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required. Respirator with filter for organic vapor.

EYE PROTECTION: Safety glasses.
HAND PROTECTION: Impervious gloves.
Body Protection: Long sleeved clothing.

Remove and wash contaminated clothing before re-use.

#### **OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

# 9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Amber to slight green

Physical State Liquid

Odor threshold Slight ammonia

Not determined

**pH** Alkaline

Melting point / freezing point (°C)

Not determined

Boiling point/range (°C) 64 - N.D.

Flash Point, (°F / °C) 224F / 107C

Evaporation rate Not determined

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive N/A - N/A

limits

Vapour PressureNot determinedVapour densityNot determinedRelative densityNot determined

Solubility in / Miscibility with water Negligible

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity 250 CPS
Explosive properties Not applicable

Oxidising properties

Not applicable

9.2 Other information

VOC Content g/l: 5.0

Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

Specific Gravity (g/cm3) 1.049

# 10. Stability and Reactivity

#### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under normal conditions.

# 10.3 Possibility of hazardous reactions

Hazardous polymerisation may occur.

#### 10.4 Conditions to avoid

Direct sources of heat.

## 10.5 Incompatible materials

Strong oxidizing agents.

#### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

# 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: No information Inhalation LC50: No information

Irritation: No information available.

Corrosive to eyes and skin.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

**Toxicity for reproduction:** No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
111-40-0	Diethylenetriamine	1080 mg/kg, oral, rat	1090 mg/kg	10 mg/L / 1 hour, inh, rat	0.000	0.000
2855-13-2	3-aminomethyl-3,5,5- trimethylcyclohexylamine	1030 mg/kg, rat	>2000 mg/kg, rat		0.000	5.01 mg/l, 4 hr, rat
80-05-7	4,4'-isopropylidenediphenol	3250 mg/kg, oral, rat	3000 mg/kg, oral, rabbit		0.000	0.000
31326-29-1	4,4' - isopropylidenediphenol oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with dietheylenetriamine	540 mg/kg, oral (rat)	1494 mg/kg, rabbit		0.000	0.000
100-51-6	Benzyl alcohol	1620 mg/kg, rat	2000 mg/kg, rabbit	4.178 mg/l, rat, 4h	0.000	4.178 mg/l,4h, rat

#### **Additional Information:**

This product is classified as a "Acute Toxicity, Inhalation, Category 1" due to containing Diethylenetriamine (CAS # 111-40-0). Numerous Industrial Hygiene air monitoring studies have been conducted by Stonhard to determine actual levels of exposure to Diethylenetriamine during product installations to application personnel. In each case levels of exposure were found to be well below the ACGIH Threshold Limit Value and NIOSH Recommended Exposure Limit of 1 ppm.

# 12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

**12.4 Mobility in soil:** No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

**12.6 Other adverse effects:** No information

CAS-No.	Chemical Name	EC50 48hr	IC50 72hr	LC50 96hr
111-40-0	Diethylenetriamine	780 mg/l	No information	430 mg/l
2855-13-2	3-aminomethyl-3,5,5- trimethylcyclohexylamine	23 mg/l	>50 mg/l	110 mg/l
80-05-7	4,4'-isopropylidenediphenol	10.2 mg/l	No information	205 mg/l
31326-29-1	4,4' - isopropylidenediphenol oligomeric reaction products with 1-chloro-2,3-epoxypropane, reaction products with dietheylenetriamine	No information	No information	
100-51-6	Benzyl alcohol	230 mg/l	700 mg/l	460 mg/l
1760-24-3	N-(3-(trimethoxysilyl)propyl)ethylenediamine	No information	No information	

# 13. Disposal Considerations

**13.1 WASTE TREATMENT METHODS:** If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport Information

**14.1 UN number** UN2735

**14.2 UN proper shipping name** Amines, liquid, corrosive, n.o.s.

Technical name Cycloaliphatic amine, Diethylenetriamine

14.3 Transport hazard class(es) 8

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5 Environmental hazards Not applicable
14.6 Special precautions for user EmS-No.:
F-A, S-B

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

# 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

# U.S. Federal Regulations: As follows -

## **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

<u>Chemical Name</u> <u>CAS-No.</u> <u>%</u>

4,4'-isopropylidenediphenol 80-05-7 14.25

### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical NameCAS-No.Ethylenediamine107-15-3

#### U.S. Clean Air Act:

EPA Coating Category: Industrial Maintenance Coating

EPA VOC Content Limit (g/l): 450
Product VOC Content (g/l) 5.0
Thinning Recommendations: None

Application Recommendations: For professional use only.

# U.S. State Regulations: As follows -

## New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

## <u>Chemical Name</u> <u>CAS-No.</u>

No NJ Right-To-Know components exist in this product.

# Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

# California Proposition 65:

WARNING: Reproductive Toxicant -- www.P65Warnings.ca.gov

No Proposition 65 Carcinogens exist in this product.

# International Regulations: As follows -

## \* Canadian DSL:

All chemical ingredients included on inventory or exempt.

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

<sup>\*</sup> As per the federal EPA definition for coating categories in 40 CFR 59.401.

<sup>\*\*</sup> Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

# Other Information

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

	•
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H360F	May damage fertility.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects.

#### Reasons for revision

Substance and/or Product Properties Changed in Section(s):

- 01 Identification
- 03 Composition/Information On Ingredients
  08 Exposure Controls/Personal Protection
- 11 Toxicological Information 15 - Regulatory Information Substance Chemical Name Changed Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

## Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit

OEL Occupational exposure limit

ppm Parts per million
mg/m3 Milligrams per cubic meter
TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu m$ .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.