

**Safety Data Sheet**

Prepared In Accordance With HCS 29  
C.F.R. 1910.1200

**STONHARD****1. Identification of the Substance/Mixture and the Company/Undertaking**

- 1.1 Product Identifier** 55700B-0001 **Revision Date:** 05/27/2025  
**Product Name:** Stonchem 700 Topcoat Gray Resin **Supersedes Date:** 04/25/2025
- 1.2 Relevant identified uses of the substance or mixture and uses advised against** Base component of 2 components coating - Industrial use. Advised against: others than recommended
- 1.3 Details of the supplier of the safety data sheet**
- Manufacturer:** Stonhard, Division of StonCor Group, Inc.  
1000 East Park Avenue  
Maple Shade, NJ 08052  
  
+1 856 7797500 (US)
- Datasheet Produced by:** ehs@stonhard.com
- 1.4 Emergency telephone number:** +1 703-741-5970 - North America  
+1 800-424-9300  
+55 11 4349 1359 - South America  
+52 55 8526 4930 - Central America  
+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, And Africa  
+65 3163 8374 - Asia, South Asia, And Oceania

**2. Hazard Identification****2.1 Classification of the substance or mixture**

Acute Toxicity, Inhalation, category 4  
Hazardous to the aquatic environment, Chronic, category 3  
Carcinogenicity, category 1A  
Eye Irritation, category 2A  
Flammable Liquid, category 3  
Germ Cell Mutagenicity, category 1B  
Reproductive\_ToxicityD\_category\_2  
Skin Irritation, category 2  
STOT, single exposure, category 1

## 2.2 Label elements

### Symbol(s) of Product



### Signal Word

Danger

### Named Chemicals on Label

Styrene, quartz (silicon dioxide), Naphtha (petroleum), hydrodesulfurized heavy, SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED

### HAZARD STATEMENTS

|   |         |  |
|---|---------|--|
| Flammable Liquid, category 3                              | H226    | Flammable liquid and vapour.                       |
| Skin Irritation, category 2                               | H315    | Causes skin irritation.                            |
| Eye Irritation, category 2A                               | H319    | Causes serious eye irritation.                     |
| Acute Toxicity, Inhalation, category 4                    | H332    | Harmful if inhaled.                                |
| Germ Cell Mutagenicity, category 1B                       | H340-1B | May cause genetic defects.                         |
| Carcinogenicity, category 1A                              | H350-1A | May cause cancer.                                  |
| Reproductive_ToxicityD_category_2                         | H361d   | Suspected of damaging the unborn child.            |
| STOT, single exposure, category 1                         | H370    | Causes damage to organs.                           |
| Hazardous to the aquatic environment, Chronic, category 3 | H412    | Harmful to aquatic life with long lasting effects. |

### PRECAUTION PHRASES

|              |   |
|--------------|---|
| P201         | Obtain special instructions before use.   |
| P202         | Do not handle until all safety precautions have been read and understood.   |
| P210         | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                      |
| P260         | Do not breathe dust/fume/gas/mist/vapours/spray.  |
| P264         | Wash hands thoroughly after handling.   |
| P273         | Avoid release to the environment.   |
| P280         | Wear protective gloves/protective clothing/eye protection/face protection.  |
| P284         | Wear respiratory protection.  |
| P304+340     | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.                                    |
| P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. |
| P307+311     | IF exposed, call a POISON CENTER or doctor/physician.   |
| P308+313     | IF exposed or concerned: Get medical advice/attention.  |
| P312         | Call a POISON CENTER or doctor/physician if you feel unwell.  |
| P314         | Get medical advice/attention if you feel unwell.  |
| P332+313     | If skin irritation occurs: Get medical advice/attention.  |
| P337+313     | If eye irritation persists: Get medical advice/attention.   |
| P403+233     | Store in a well-ventilated place. Keep container tightly closed.  |

**2.3 Other hazards**

No Information

**Results of PBT and vPvB assessment:**

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

**3. Composition/Information On Ingredients****3.2 Mixtures****Hazardous ingredients**

| <u>Name According to EEC</u>  | <u>EINEC No.</u> | <u>CAS-No.</u> | <u>%</u>   | <u>Classifications</u>        |   |
|---|------------------|----------------|------------|-------------------------------|---|
| Styrene   | 202-851-5        | 100-42-5       | 10 - <25   | H226-315-319-332-3<br>61d-372 | Acute Tox. 4 Inhalation, Eye Irrit. 2, Flam. Liq. 3, Repr. 2, Skin Irrit. 2, STOT RE 1          |
| quartz (silicon dioxide)  | 238-878-4        | 14808-60-7     | 10 - <25   | H350-370                      | Carc. 1A, STOT SE 1   |
| titanium dioxide  | 236-675-5        | 13463-67-7     | 1.0 - <2.5 | H351                          | Carc. 2   |
| SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED | 265-199-0        | 64742-95-6     | 0.1 - <1.0 | H304-332-335-336-3<br>40-350  | Acute Tox. 4 Inhalation, Asp. Tox. 1, Carc. 1B, Muta. 1B, STOT SE 3 NE, STOT SE 3 RTI           |
| Naphtha (petroleum), hydrodesulfurized heavy                                      | 265-185-4        | 64742-82-1     | 0.1 - <1.0 | H304-331-336-372-4<br>11      | Acute Tox. 3 Inhalation, Aquatic Chronic 2, Asp. Tox. 1, Skin Cracking, STOT RE 1, STOT SE 3 NE |

CAS-No.M-Factors

100-42-5  
14808-60-7  
13463-67-7  
64742-95-6  
64742-82-1

**Additional Information:**

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

**4. First-aid Measures****4.1 Description of First Aid Measures****GENERAL NOTES:** When symptoms persist or in all cases of doubt seek medical advice.**AFTER INHALATION:** Move to fresh air. Consult a physician after significant exposure.**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.**Self protection of the first aider:**

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

**4.2 Most important symptoms and effects, both acute and delayed**

Harmful by inhalation. Irritating to eyes. Harmful in contact with skin and if swallowed.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

### 5. Fire-fighting Measures

#### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

**FOR SAFETY REASONS NOT TO BE USED:** Alcohol, Alcohol based solutions, any other media not listed above.

#### 5.2 Special hazards arising from the substance or mixture

Flammable.

#### 5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

### 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

#### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

### 7. Handling and Storage

#### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

**PROTECTION AND HYGIENE MEASURES:** Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Direct sources of heat.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### 7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

## 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits (US)

| <u>Name</u>   | <u>CAS-No.</u> | <u>ACGIH TWA</u>                                  | <u>ACGIH STEL</u> | <u>ACGIH Ceiling</u> |
|---|----------------|---|-------------------|----------------------|
| Styrene   | 100-42-5       | 10 PPM  | 20 PPM            |                      |
| quartz (silicon dioxide)  | 14808-60-7     | 0.025 MGM3  |                   |                      |
| titanium dioxide  | 13463-67-7     | 10 MGM3 2.5 MGM3<br>2.5 MGM3 0.2<br>MGM3 0.2 MGM3 |                   |                      |
| SOLVENT NAPHTHA (PETROLEUM),<br>LIGHT AROM.; LOW BOILING POINT<br>NAPHTHA - UNSPECIFIED | 64742-95-6     | 300.0 PPM   |                   |                      |
| Naphtha (petroleum), hydrodesulfurized<br>heavy   | 64742-82-1     |   |                   |                      |

| <u>Name</u>   | <u>CAS-No.</u> | <u>OSHA PEL</u>  | <u>OSHA STEL</u>  |
|---|----------------|------------------|-------------------|
| Styrene   | 100-42-5       | 215 MGM3, 50 PPM | 425 MGM3, 100 PPM |
| quartz (silicon dioxide)  | 14808-60-7     | 0.05 MGM3        |                   |
| titanium dioxide  | 13463-67-7     | 15 MGM3          |                   |
| SOLVENT NAPHTHA (PETROLEUM),<br>LIGHT AROM.; LOW BOILING POINT<br>NAPHTHA - UNSPECIFIED | 64742-95-6     |                  |                   |
| Naphtha (petroleum), hydrodesulfurized<br>heavy   | 64742-82-1     | 2900 mg/m3       |                   |

**FURTHER INFORMATION:** Refer to the regulatory exposure limits for the workforce enforced in each country.

### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** Respirator with filter for organic vapor.

**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses. Safety goggles.

**HAND PROTECTION:** Impervious gloves.

**Body Protection:** Long sleeved clothing.

Remove and wash contaminated clothing before re-use.

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

|                |                |
|----------------|----------------|
| Appearance:    | GRAY           |
| Physical State | LIQUID         |
| Odor           | Solvent like   |
| Odor threshold | Not determined |
| pH             | Non-aqueous    |

|  |                                 |
|--|---------------------------------|
| Melting point / freezing point (°C)          | Not determined                  |
| Boiling point/range (°C)                     | 56 - N.D.                       |
| Flash Point, (°F / °C)                       | 73F / 23C                       |
| Evaporation rate                             | Not determined                  |
| Flammability (solid, gas)                    | Not determined                  |
| Upper/lower flammability or explosive limits | Not determined - Not determined |
| Vapour Pressure                              | Not determined                  |
| Vapour density                               | Not determined                  |
| Relative density                             | Not determined                  |
| Solubility in / Miscibility with water       | NIL                             |
| Partition coefficient: n-octanol/water       | Not determined                  |
| Auto-ignition temperature (°C)               | Not determined                  |
| Decomposition temperature (°C)               | Not determined                  |
| Viscosity                                    | 16600 CPS                       |
| Explosive properties                         | Not determined                  |
| Oxidising properties                         | Not determined                  |

**9.2 Other information**

|  |       |
|--|-------|
| VOC Content g/l:   | 41    |
| Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E. |       |
| Specific Gravity (g/cm3)   | 1.563 |

## 10. Stability and Reactivity

**10.1 Reactivity**

No reactivity hazards known under normal storage and use conditions.

**10.2 Chemical stability**

Stable under recommended storage conditions. Risk of ignition.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation does not occur.

**10.4 Conditions to avoid**

Direct sources of heat.

**10.5 Incompatible materials**

Strong oxidizing agents.

**10.6 Hazardous decomposition products**

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

## 11. Toxicological Information

### 11.1 Information on toxicological effects

**Acute Toxicity:**

**Oral LD50:** No information

**Inhalation LC50:** No information

**Irritation:** No information available.

**Corrosivity:** No information available.

**Sensitization:** No information available.

**Repeated dose toxicity:** No information available.

**Carcinogenicity:** No information available.

**Mutagenicity:** No information available.

**Toxicity for reproduction:** No information available.

**STOT-single exposure:** No information available.

**STOT-repeated exposure:** No information available.

**Aspiration hazard:** No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.  
Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>   | <u>Oral LD50</u>           | <u>Dermal LD50</u>     | <u>Vapor LC50</u>                       | <u>Gas LC50</u>        | <u>Dust/Mist LC50</u> |
|----------------|--|----------------------------|------------------------|---|------------------------|-----------------------|
| 100-42-5       | Styrene  | 2650 mg/kg                 | >2000 mg/kg            | 2770 ppm, 4 h                           | 0.000                  | 0.000                 |
| 14808-60-7     | quartz (silicon dioxide)   | >2000 mg/kg                |                        |   | 0.000                  | 0.000                 |
| 13463-67-7     | titanium dioxide   | 10000 mg/kg,<br>oral (rat) |                        |   | 0.000                  | 6,82 mg/l (rat)<br>4h |
| 64742-95-6     | SOLVENT NAPHTHA<br>(PETROLEUM), LIGHT AROM.;<br>LOW BOILING POINT<br>NAPHTHA - UNSPECIFIED | 4610 mg/kg,<br>oral, rat   | >3480 mg/kg,<br>rabbit | 3670 ppm/4<br>hours, rat,<br>inhalation | 3670 ppm, rat,<br>4hrs | 0.000                 |
| 64742-82-1     | Naphtha (petroleum),<br>hydrodesulfurized heavy  | >2000 mg/kg,<br>rat, oral  |                        | 5 mg/l/4h (rat)                         | 0.000                  | 0.000                 |

**Additional Information:**

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form or progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other silicates as impurities, and above dei minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems. This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

## 12. Ecological Information

**12.1 Toxicity:**

|                      |                |
|----------------------|----------------|
| EC50 48hr (Daphnia): | No information |
| IC50 72hr (Algae):   | No information |
| LC50 96hr (fish):    | No information |

**12.2 Persistence and degradability:** No information

**12.3 Bioaccumulative potential:** No information

**12.4 Mobility in soil:** No information

**12.5 Results of PBT and vPvB assessment:** The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

**12.6 Other adverse effects:** No information

| <u>CAS-No.</u> | <u>Chemical Name</u>  | <u>EC50 48hr</u>                                  | <u>IC50 72hr</u> | <u>LC50 96hr</u> |
|----------------|---|---|------------------|------------------|
| 100-42-5       | Styrene   | 4.7 mg/l  | No information   | 4.02 mg/l        |
| 14808-60-7     | quartz (silicon dioxide)  | No information                                    | No information   |                  |
| 13463-67-7     | titanium dioxide  | >100 mg/l (EC50, 48h, Daphnia magna OECD202)ation | No information   | >1000 mg/l       |
| 64742-95-6     | SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED | >1 - 10 mg/l                                      | >1 - 10 mg/l     | >10-100 mg/l     |
| 64742-82-1     | Naphtha (petroleum), hydrodesulfurized heavy                                      | No information                                    | No information   |                  |

## 13. Disposal Considerations

**13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.



## 14. Transport Information

|      |  |                 |
|------|--|-----------------|
| 14.1 | UN number  | UN1866          |
| 14.2 | UN proper shipping name  | Resin Solution  |
|      | Technical name   | Not applicable  |
| 14.3 | Transport hazard class(es)   | 3               |
|      | Subsidiary shipping hazard   | Not applicable  |
| 14.4 | Packing group  | III             |
| 14.5 | Environmental hazards  | Not applicable  |
| 14.6 | Special precautions for user   | Not applicable  |
|      | EmS-No.:   | F-E, <u>S-D</u> |
| 14.7 | Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code | Not applicable  |

## 15. Regulatory Information

- 15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

### U.S. Federal Regulations: As follows -

#### CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Germ cell mutagenicity

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

| <u>Chemical Name</u> | <u>CAS-No.</u> | <u>%</u> |
|----------------------|----------------|----------|
| Styrene              | 100-42-5       | 19.41    |
| Acetone              | 67-64-1        | 0.45     |
| N,N-diethylaniline   | 91-66-7        | 0.27     |
| Toluene              | 108-88-3       | 0        |
| Benzene              | 71-43-2        | 0        |
| Aniline              | 62-53-3        | 0        |

**Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

| <u>Chemical Name</u>         | <u>CAS-No.</u> |
|------------------------------|----------------|
| 1,6 hexandiol glycidyl ether | 16096-31-4     |

**U.S. Clean Air Act:**

|                              |                                 |
|------------------------------|---------------------------------|
| EPA Coating Category:        | Industrial Maintenance Coatings |
| EPA VOC Content Limit (g/l): | 450                             |
| Product VOC Content (g/l)    | 41                              |
| Thinning Recommendations:    | None                            |
| Application Recommendations: | For professional use only.      |

\* As per the federal EPA definition for coating categories in 40 CFR 59.401.

\*\* Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

**U.S. State Regulations: As follows -****New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| glass oxide          | 65997-17-3     |
| Polyester Resin      | 800963-5025    |

**Pennsylvania Right-To-Know**

The following non-hazardous ingredients are present in the product at greater than 3%.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| glass oxide          | 65997-17-3     |
| Polyester Resin      | 800963-5025    |

**California Proposition 65:**

WARNING: Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

WARNING: Reproductive Toxicant -- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**International Regulations: As follows -****\* Canadian DSL:**

All chemical ingredients included on inventory or exempt.

**15.2 Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## 16. Other Information

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

|       |   |
|-------|---|
| H226  | Flammable liquid and vapour.                                    |
| H304  | May be fatal if swallowed and enters airways.                   |
| H315  | Causes skin irritation.   |
| H319  | Causes serious eye irritation.                                  |
| H331  | Toxic if inhaled.   |
| H332  | Harmful if inhaled.   |
| H335  | May cause respiratory irritation.                               |
| H336  | May cause drowsiness or dizziness.                              |
| H340  | May cause genetic defects.                                      |
| H350  | May cause cancer.   |
| H351  | Suspected of causing cancer.                                    |
| H361d | Suspected of damaging the unborn child.                         |
| H370  | Causes damage to organs.  |
| H372  | Causes damage to organs through prolonged or repeated exposure. |
| H411  | Toxic to aquatic life with long lasting effects.                |

### Reasons for revision

Substance Regulatory CAS Number Changed

Substance and/or Product Properties Changed in Section(s):

- 01 - Identification
- 08 - Exposure Controls/Personal Protection

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

### List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

### Acronym & Abbreviation Key:

|        |  |
|--------|--|
| CLP    | Classification, Labeling & Packaging Regulation                        |
| EC     | European Commission  |
| EU     | European Union   |
| US     | United States  |
| CAS    | Chemical Abstract Service  |
| EINECS | European Inventory of Existing Chemical Substances                     |
| REACH  | Registration, Evaluation, Authorization of Chemicals Regulation        |
| GHS    | Globally Harmonized System of Classification and Labeling of Chemicals |
| LTEL   | Long term exposure limit   |
| STEL   | Short term exposure limit  |
| OEL    | Occupational exposure limit  |
| ppm    | Parts per million  |

|                   |   |
|-------------------|---|
| mg/m <sup>3</sup> | Milligrams per cubic meter  |
| TLV               | Threshold Limit Value   |
| ACGIH             | American Conference of Governmental Industrial Hygienists   |
| OSHA              | Occupational Safety & Health Administration   |
| PEL               | Permissible Exposure Limits   |
| VOC               | Volatile organic compounds  |
| g/l               | Grams per liter   |
| mg/kg             | Milligrams per kilogram   |
| N/A               | Not applicable  |
| LD <sub>50</sub>  | Lethal dose at 50%  |
| LC <sub>50</sub>  | Lethal concentration at 50%   |
| EC <sub>50</sub>  | Half maximal effective concentration  |
| IC <sub>50</sub>  | Half maximal inhibitory concentration   |
| PBT               | Persistent bioaccumulative toxic chemical   |
| vPvB              | Very persistent and very bioaccumulative  |
| EEC               | European Economic Community   |
| ADR               | International Transport of Dangerous Goods by Road  |
| RID               | International Transport of Dangerous Goods by Rail  |
| UN                | United Nations  |
| IMDG              | International Maritime Dangerous Goods Code   |
| IATA              | International Air Transport Association   |
| MARPOL            | International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978   |
| IBC               | International Bulk Container  |
| RTI               | Respiratory Tract Irritation  |
| NE                | Narcotic Effects  |
| IMO               | International Maritime Organization   |
| Note P:           | The classification as a carcinogen or mutagen need not apply; the substance contains less than 0,1 % w/w benzene  |
| Note 10:          | The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter ≤ 10 µm. |

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

