Safety Data Sheet

Prepared In Accordance With HCS 29 C.F.R. 1910.1200



1. Identification of the Substance/Mixture and the Company/Undertaking

66780 **Revision Date:** 05/27/2025 1.1 Product Identifier

Supersedes Date: 06/18/2024 STONCHEM 700/800 PRIMER **Product Name:**

RESIN

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Base component of 2 components coating - Industrial use. Advised against: others than

recommended

1.3 Details of the supplier of the safety data sheet

> Stonhard, Division of StonCor Group, Inc. Manufacturer:

1000 East Park Avenue Maple Shade, NJ 08052

+1 856 7797500 (US)

ehs@stonhard.com **Datasheet Produced by:**

1.4 +1 703-741-5970 - North America Emergency telephone number:

+1 800-424-9300

+55 11 4349 1359 - South America +52 55 8526 4930 - Central America

+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, And Africa

+65 3163 8374 - Asia, South Asia, And Oceania

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Hazardous to the aquatic environment, Chronic, category 3 Carcinogenicity, category 1B Eye Irritation, category 2A Flammable Liquid, category 3 Germ Cell Mutagenicity, category 1B Organic Peroxide, categories E, F Reproductive_ToxicityD_category_2 Skin Irritation, category 2 STOT, repeated exposure, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Styrene, Naphtha (petroleum), hydrodesulfurized heavy, SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW **BOILING POINT NAPHTHA - UNSPECIFIED**

Flammable liquid and vapour.

H226

HAZARD STATEMENTS

Flammable Liquid, category 3

· ·a·····ab··· = ·qa··a, varogo·· , v		the state of the s
Organic Peroxide, categories E, F	H242-EF	Heating may cause a fire.
Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Germ Cell Mutagenicity, category 1B	H340-1B	May cause genetic defects.
Carcinogenicity, category 1B	H350-1B	May cause cancer.
Reproductive_ToxicityD_category_2	H361d	Suspected of damaging the unborn child.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P234	Keep only in original packaging.
	P235	Keep cool.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P264	Wash hands thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P284	Wear respiratory protection.

P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P332+313	If skin irritation occurs: Get medical advice/attention.
P337+313	If eye irritation persists: Get medical advice/attention.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients 3.2 **Mixtures** Hazardous ingredients Name According to EEC **EINEC No.** CAS-No. <u>%</u> Classifications 202-851-5 100-42-5 25 - < 50 H226-315-319-332-3 Styrene Acute Tox. 4 Inhalation, Eye 61d-372 Irrit. 2, Flam. Liq. 3, Repr. 2, Skin Irrit. 2, STOT RE 1 215-325-5 1321-74-0 2.5 - < 10 Aquatic Chronic 2, Eye Irrit. divinyl benzene H315-319-335-411 2, Skin Irrit. 2, STOT SE 3 RTI 2.5 - < 10 Ethylstyrene 28106-30-1 Naphtha (petroleum), 265-185-4 64742-82-1 0.1 - < 1.0H304-331-336-372-4 Acute Tox. 3 Inhalation, hydrodesülfurized Aquatic Chronic 2, Asp. Tox. 11 heavy 1, Skin Cracking, STOT RE 1, STOT SE 3 NE **SOLVENT NAPHTHA** 265-199-0 64742-95-6 0.1 - < 1.0 H304-332-335-336-3 Acute Tox. 4 Inhalation, Asp. (PETROLEUM), LIGHT 40-350 Tox. 1, Carc. 1B, Muta. 1B, AROM.; LOW BOILING STOT SE 3 NE, STOT SE 3 POINT NAPHTHA -RTI **UNSPECIFIED**

61789-51-3

CAS-No. M-Factors
100-42-5
1321-74-0
28106-30-1
64742-82-1

263-064-0

64742-95-6 61789-51-3

salt

Additional Information:

naphthenic acids, cobalt

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

0.1 - < 1.0

H317-411

Aquatic Chronic 2, Skin

Sens. 1

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Harmful by inhalation. Irritating to eyes. Harmful in contact with skin and if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

Flammable.

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. High volume water jet. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive

concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
Styrene	100-42-5	10 PPM	20 PPM	
divinyl benzene	1321-74-0	10 PPM		
Ethylstyrene	28106-30-1			
Naphtha (petroleum), hydrodesulfurize heavy	ed 64742-82-1			
SOLVENT NAPHTHA (PETROLEUM LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED	,, 0., 00 0	300.0 PPM		
naphthenic acids, cobalt salt	61789-51-3			

Name	CAS-No.	OSHA PEL	OSHA STEL
Styrene	100-42-5	215 MGM3, 50 PPM	425 MGM3, 100 PPM
divinyl benzene	1321-74-0	50 MGM3, 10 PPM	
Ethylstyrene	28106-30-1		
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	2900 mg/m3	
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED	64742-95-6		
naphthenic acids, cobalt salt	61789-51-3		

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter. Respirator with filter for organic vapor.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses.

Safety goggles.

HAND PROTECTION: Impervious gloves. Body Protection: Long sleeved clothing.

Remove and wash contaminated clothing before re-use. **OTHER PROTECTIVE EQUIPMENT:** No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined

areas.

9. Physical and Chemical Properties

Information on basic physical and chemical properties 9.1

> Appearance: Not determined

Physical State LIQUID

Odor Not determined

Odor threshold Not determined

Hq Not determined

Melting point / freezing point (°C) Not determined

Boiling point/range (°C) 56 - N.D.

Flash Point, (°F / °C) >73F / >23C

Evaporation rate Not determined

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive

Not determined

Vapour Pressure Not determined

Vapour density Not determined

Relative density Not determined

Solubility in / Miscibility with water Not determined

Partition coefficient: n-octanol/water Not determined

Auto-ignition temperature (°C) Not determined

Decomposition temperature (°C) Not determined

Viscosity Not determined

Not determined **Explosive properties**

Oxidising properties

Not determined

9.2 Other information

> VOC Content g/l: Not determined

Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

0.000 Specific Gravity (g/cm3)

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information Inhalation LC50: No information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
100-42-5	Styrene	2650 mg/kg	>2000 mg/kg	2770 ppm, 4 h	0.000	0.000
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	>2000 mg/kg, rat, oral		5 mg/l/4h (rat)	0.000	0.000
64742-95-6	SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED	4610 mg/kg, oral, rat	>3480 mg/kg, rabbit	3670 ppm/4 hours, rat, inhalation	3670 ppm, rat, 4hrs	0.000
61789-51-3	naphthenic acids, cobalt salt	3900 mg/kg, oral, rat			0.000	0.000

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information

CAS-No.	<u>Chemical Name</u>	EC50 48hr	IC50 72hr	LC50 96hr
100-42-5	Styrene	4.7 mg/l	No information	4.02 mg/l
1321-74-0	divinyl benzene	No information	No information	
28106-30-1	Ethylstyrene	No information	No information	
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	No information	No information	
64742-95-6	SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED	>1 - 10 mg/l	>1 - 10 mg/l	>10-100 mg/l
61789-51-3	naphthenic acids, cobalt salt	No information	No information	

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1UN numberUN186614.2UN proper shipping nameResin SolutionTechnical nameNot applicable14.3Transport hazard class(es)3

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5 Environmental hazards
14.6 Special precautions for user
EmS-No.:
14.7 Transport in bulk according to Annex II of
Not applicable
F-E, S-D
Not applicable
Not applicable

MARPOL 73/78 and the IBC code

15. Regulatory Information

15.1

Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Organic peroxide, Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Germ cell mutagenicity

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

Chemical Name	<u>CAS-No.</u>	<u>%</u>	
Styrene	100-42-5	28.25	
Acetone	67-64-1	0.45	
N,N-diethylaniline	91-66-7	0.28	
Toluene	108-88-3	0	
Benzene	71-43-2	0	
Aniline	62-53-3	0	

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category:

EPA VOC Content Limit (g/l):

Product VOC Content (g/l)

Thinning Recommendations:

Application Recommendations:

Not applicable

Not applicable

^{*} As per the federal EPA definition for coating categories in 40 CFR 59.401.

^{**} Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>CAS-No.</u>

 Vinyl Ester Resin (proprietary)
 18275200000-5274

 mixture - trade secret
 18275200000-5009

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u> <u>CAS-No.</u>

Vinyl Ester Resin (proprietary) 18275200000-5274

California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov

WARNING: Reproductive Toxicant -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.

H350 May cause cancer.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Reasons for revision

Composition Information Changed

Substance and/or Product Properties Changed in Section(s):

01 - Identification

08 - Exposure Controls/Personal Protection

15 - Regulatory Information Substance CAS Number Changed Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter \leq 10 μm_{\star}

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.