Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200



1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 618XA0 Revision Date: 06/17/2024

Product Name: STONGLAZE E4 AMINE Supersedes Date: 05/13/2024

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Hardener for 2 components coatings - Industrial use. Advised against: others than

recommended

1.3 Details of the supplier of the safety data sheet

Manufacturer: Stonhard, Division of StonCor Group, Inc.

1000 East Park Avenue Maple Shade, NJ 08052

+1 856 7797500 (US)

Datasheet Produced by: ehs@stonhard.com

1.4 Emergency telephone number: +1 703-741-5970 - North America

+1 800-424-9300

+55 11 4349 1359 - South America +52 55 8526 4930 - Central America

+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa

+65 3163 8374 - Asia, South Asia, And Oceania

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 3
Hazardous to the aquatic environment, Chronic, category 3
Skin Corrosion, category 1
Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Benzyl alcohol, Isophoronediamine, trimethyl 1-1,6-hexanediamine

H302

HAZARD STATEMENTS

Acute Toxicity, Oral, category 4

| Skin Corrosion, category 1 | H314-1 | Causes severe skin burns and eye damage. |
|---|--------------|--|
| Skin Sensitizer, category 1 | H317 | May cause an allergic skin reaction. |
| Acute Toxicity, Inhalation, category 3 | H331 | Toxic if inhaled. |
| Hazardous to the aquatic environment, Chronic, category 3 | H412 | Harmful to aquatic life with long lasting effects. |
| PRECAUTION PHRASES | | |
| | P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| | P264 | Wash hands thoroughly after handling. |
| | P270 | Do no eat, drink or smoke when using this product. |
| | P273 | Avoid release to the environment. |
| | P280 | Wear protective gloves/protective clothing/eye protection/ face protection. |
| | P301+310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| | P301+330+331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. |
| | P302+352 | IF ON SKIN: Wash with plenty of soap and water. |
| | P304+340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| | | |

P305+351+338

P333+313 P363 Harmful if swallowed.

Continue rinsing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

No information

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

| Name According to EEC | EINEC No. | CAS-No. | <u>%</u> | <u>Classifications</u> | |
|-----------------------|-----------|----------|----------|------------------------|---|
| Benzyl alcohol | 202-859-9 | 100-51-6 | 25 - <50 | | Acute Tox. 3 Inhalation, Acute Tox. 4 Dermal, Acute Tox. 4 Oral, Eye Irrit. 2 |

| cyclohexanemethanami ne, 5-amino-1,3,3- trimethyl-, reaction products with bisphenol a diglycidyl ether homopolymer | 614-657-1 | 68609-08-5 | 10 - <25 | H411 | Aquatic Chronic 2 |
|--|-----------|------------|------------|------------------|---|
| Isophoronediamine | 220-666-8 | 2855-13-2 | 10 - <25 | H302-314-317-412 | Acute Tox. 4 Oral, Aquatic Chronic 3, Skin Corr. 1B, Skin Sens. 1 |
| trimethyl 1-1,6- hexanediamine | 247-134-8 | 25620-58-0 | 2.5 - <10 | H302-314-317-412 | Acute Tox. 4 Oral, Aquatic Chronic 3, Skin Corr. 1, Skin Sens. 1 |
| octadecyl 3,5-di-tert- butyl-4- | 218-216-0 | 2082-79-3 | 1.0 - <2.5 | | |

Product: 618XA0

CAS-No.

M-Factors

100-51-6 68609-08-5 2855-13-2 25620-58-0 2082-79-3

Additional Information:

Date Printed: 06/17/2024

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Causes severe burns. Harmful in contact with skin and if swallowed. Irritating to eyes and respiratory system.

4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention is required. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Do not breathe vapours or spray mist.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

| <u>Name</u> | CAS-No. | ACGIH TWA | ACGIH STEL | ACGIH Ceiling |
|--|-------------------|------------|------------|---------------|
| Benzyl alcohol | 100-51-6 | | | |
| cyclohexanemethanamine, 5- amino-1,3,3-trimethyl-, reaction produ with bisphenol a diglycidyl ether homopolymer | 68609-08-5 cts | | | |
| Isophoronediamine | 2855-13-2 | | | |
| trimethyl 1-1,6-hexanediamine | 25620-58-0 | | | |
| octadecyl 3,5-di-tert-butyl-4- | 2082-79-3 | 10.0 MG/M3 | | |

CAS-No. OSHA PEL **OSHA STEL Name**

Benzyl alcohol 100-51-6

cyclohexanemethanamine, 5-68609-08-5

amino-1,3,3-trimethyl-, reaction products with bisphenol a diglycidyl ether

homopolymer

Isophoronediamine 2855-13-2

trimethyl 1-1,6-hexanediamine 25620-58-0

15.0 MG/M3 octadecyl 3,5-di-tert-butyl-4-2082-79-3

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.

EYE PROTECTION: Safety glasses.

HAND PROTECTION: Impervious gloves. Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined

Not determined

areas.

Physical and Chemical Properties

Information on basic physical and chemical properties 9.1

> Appearance: Clear / Amber

Physical State LIQUID

Odor Ammonical

Odor threshold Not determined

pН Non-aqueous

Melting point / freezing point (°C) Not determined

Boiling point/range (°C) N.D. - N.D.

Flash Point, (°F / °C) >201F / >94C

Evaporation rate

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive N/A - N/A

limits

Vapour Pressure 0.1 mmHg @ 20C

Vapour density 3.72 mmHg

Relative density Not determined

<4% Solubility in / Miscibility with water

Partition coefficient: n-octanol/water Not determined Auto-ignition temperature (°C) Not determined Decomposition temperature (°C) Not determined

Viscosity 4000 cps

Page 5 / 12

Explosive properties N/A

Oxidising properties N/A

9.2 Other information

VOC Content g/l: 39

Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

Specific Gravity (g/cm3) 0.943

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation may occur.

10.4 Conditions to avoid

Direct sources of heat.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information Inhalation LC50: No information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 | Gas LC50 | Dust/Mist LC50 |
|------------|-------------------------------|-------------------------|-----------------------|------------------------|----------|-----------------------|
| 100-51-6 | Benzyl alcohol | 1620 mg/kg, rat | 2000 mg/kg, rabbit | 4.178 mg/l, rat, 4h | 0.000 | 4.178 mg/l,4h, rat |
| 2855-13-2 | Isophoronediamine | 1030 mg/kg, rat | >2000 mg/kg, rat | | 0.000 | 5.01 mg/l 4 hr |
| 25620-58-0 | trimethyl 1-1,6-hexanediamine | 910 mg/kg, oral, rat | | | 0.000 | 0.000 |

Additional Information:

No Information

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB No information

assessment:

12.6 Other adverse effects: No information

| CAS-No. | <u>Chemical Name</u> | EC50 48hr | IC50 72hr | LC50 96hr |
|------------|--|----------------|----------------|-----------|
| 100-51-6 | Benzyl alcohol | 230 mg/l | 700 mg/l | 460 mg/l |
| 68609-08-5 | cyclohexanemethanamine, 5-amino-1,3,3- trimethyl-, reaction products with bisphenol a diglycidyl ether homopolymer | No information | No information | |
| 2855-13-2 | Isophoronediamine | 23 mg/l | >50 mg/l | 110 mg/l |
| 25620-58-0 | trimethyl 1-1,6-hexanediamine | No information | No information | |
| 2082-79-3 | octadecyl 3,5-di-tert-butyl-4- | No information | No information | |

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number UN2735

14.2 UN proper shipping name Amines, Liquid, Corrosive, n.o.s

Technical name Modified Alphatic Amines. Isophoronediamine

14.3 Transport hazard class(es) 8

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5Environmental hazardsNot applicable14.6Special precautions for userNot applicableEmS-No.:F-A, S-B

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Respiratory or Skin Sensitization

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

No SARA 313 substances exist in this product above de minimis concentrations.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category: Industrial Maintenance Coating

EPA VOC Content Limit (g/l): 450
Product VOC Content (g/l) 39

Thinning Recommendations: The coating is to be applied without thinning.

Application Recommendations: For professional use only.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical NameCAS-No.glass oxide65997-17-3

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical NameCAS-No.glass oxide65997-17-3

California Proposition 65:

No Proposition 65 Chemicals exist in this product.

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

^{*} As per the federal EPA definition for coating categories in 40 CFR 59.401.

^{**} Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302
H312
H314
H314
Causes severe skin burns and eye damage.
H317
May cause an allergic skin reaction.
H319
Causes serious eye irritation.
H331
Toxic if inhaled.
H411
Toxic to aquatic life with long lasting effects.
H412
Harmful to aquatic life with long lasting effects.

Reasons for revision

Substance and/or Product Properties Changed in Section(s): 14 - Transportation Information

Changes have been made to Section 8 of the Safety Data Sheet (SDS). Please refer to the Exposure Controls / Personal Protection information in Section 8 of the SDS. This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

Classification, Labeling & Packaging Regulation CLP ЕC European Commission European Union EU United States US Chemical Abstract Service CAS European Inventory of Existing Chemical Substances EINECS Registration, Evaluation, Authorization of Chemicals Regulation REACH Globally Harmonized System of Classification and Labeling of Chemicals GHS LTEL Long term exposure limit STEL Short term exposure limit OEL Occupational exposure limit Parts per million ppm mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter \leq 10 μm .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.