Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200



1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 24000A0 Revision Date: 03/13/2024

Product Name: Stongard Membrane Amine Supersedes Date: 01/18/2024

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Base component of 2 components coating - Industrial use. Advised against: others than

recommended

1.3 Details of the supplier of the safety data sheet

Manufacturer: Stonhard, Division of StonCor Group, Inc.

1000 East Park Avenue Maple Shade, NJ 08052

+1 856 7797500 (US)

Datasheet Produced by: ehs@stonhard.com

1.4 Emergency telephone number: +1 703-741-5970 - North America

+1 800-424-9300

+55 11 4349 1359 - South America +52 55 8526 4930 - Central America

+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa

+65 3163 8374 - Asia, South Asia, And Oceania

2. Hazard Identification

2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 1 Carcinogenicity, category 1B Eye Irritation, category 2A Germ Cell Mutagenicity, category 1B Skin Irritation, category 2 Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product







Signal Word

Danger

Named Chemicals on Label

Naphtha (petroleum), heavy alkylate, 6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine

HAZARD STATEMENTS

| Skin Irritation, category 2 | H315 | Causes skin irritation. |
|--|---------|---|
| Skin Sensitizer, category 1 | H317 | May cause an allergic skin reaction. |
| Eye Irritation, category 2A | H319 | Causes serious eye irritation. |
| Germ Cell Mutagenicity, category 1B | H340-1B | May cause genetic defects. |
| Carcinogenicity, category 1B | H350-1B | May cause cancer. |
| Hazardous to the aquatic environment, Chronic, category 1 | H410 | Very toxic to aquatic life with long lasting effects. |

PRECAUTION PHRASES

| P201 | Obtain special instructions before use. |
|--------------|---|
| P202 | Do not handle until all safety precautions have been read and understood. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves/protective clothing/eye protection/ |
| | face protection. |
| P284 | Wear respiratory protection. |
| P302+352 | IF ON SKIN: Wash with plenty of soap and water. |
| P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. |
| | Remove contact lenses, if present and easy to do so. |
| | Continue rinsing. |
| P308+313 | IF exposed or concerned: Get medical advice/attention. |
| P333+313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P391 | Collect spillage. |

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

No information

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

| Name According to EEC | EINEC No. | CAS-No. | <u>%</u> | <u>Classifications</u> | |
|---|-----------|-------------|----------|------------------------|---|
| limestone | 215-279-6 | 1317-65-3 | 25 - <50 | H315-319 | Eye Irrit. 2, Skin Irrit. 2 |
| 6-methyl-2,4-bis (methylthio) phenylene-1,3-diamine | 403-240-8 | 106264-79-3 | 25 - <50 | H302-317-410 | Acute Tox. 4 Oral, Aquatic Chronic 1, Skin Sens. 1 |

| titanium dioxide | 236-675-5 | 13463-67-7 | 2.5 - <10 | H351 | Carc. 2 |
|--|-----------|------------|------------|------------------|--|
| dipropylene glycol dibenzoate | | 27138-31-4 | 1.0 - <2.5 | H412 | Aquatic Chronic 3 |
| calcium oxide | | 1305-78-8 | 1.0 - <2.5 | H315-318-335 | Eye Dam. 1, Skin Irrit. 2, STOT SE 3 RTI |
| silicon dioxide (amorphous) | 231-545-4 | 7631-86-9 | 1.0 - <2.5 | | |
| aluminum oxide | | 1344-28-1 | 1.0 - <2.5 | | |
| Naphtha (petroleum), heavy alkylate | 265-067-2 | 64741-65-7 | 1.0 - <2.5 | H226-304-340-350 | Asp. Tox. 1, Carc. 1B, Flam. Liq. 3, Muta. 1B |
| carbon black | | 1333-86-4 | 0.1 - <1.0 | | |

CAS-No.

M-Factors

1317-65-3 106264-79-3 13463-67-7 27138-31-4 1344-28-1 1305-78-8 7631-86-9 64741-65-7 1333-86-4

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: No Information **AFTER INHALATION:** Move to fresh air.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water. **AFTER EYE CONTACT:** Rinse thoroughly with plenty of water, also under the eyelids. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Do not ingest. May be harmful by inhalation, in contact with skin and if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. None.

Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: No Information

STORAGE CONDITIONS: Do not freeze. Keep containers tightly closed in a dry, cool and well-ventilated place.

7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

| <u>Name</u> | CAS-No. | ACGIH TWA | ACGIH STEL | ACGIH Ceiling |
|--|-------------|----------------------------|------------|---------------|
| limestone | 1317-65-3 | 10.00 MG/M3 | | |
| 6-methyl-2,4-bis(methylthio) phenylene-1,3-diamine | 106264-79-3 | | | |
| titanium dioxide | 13463-67-7 | 10 MGM3 10 MGM3 | | |
| dipropylene glycol dibenzoate | 27138-31-4 | | | |
| silicon dioxide (amorphous) | 7631-86-9 | 10.0 mg/m3 | | |
| aluminum oxide | 1344-28-1 | 1 mg/m3 (resp.fraction) | | |

2 MGM3 1305-78-8 calcium oxide

Naphtha (petroleum), heavy alkylate 64741-65-7

3 MGM3 carbon black 1333-86-4

Name CAS-No. OSHA PEL **OSHA STEL**

1317-65-3 5 MGM3 15 MGM3 5 limestone

MGM3 15 MGM3 5 **MGM3 15 MGM3**

6-methyl-2,4-bis(methylthio) 106264-79-3

phenylene-1,3-diamine

titanium dioxide 13463-67-7 15 MGM3

dipropylene glycol dibenzoate 27138-31-4

5 MGM3 calcium oxide 1305-78-8

0.8 mg/m3 7631-86-9 silicon dioxide (amorphous)

1344-28-1 5 MGM3 15 MGM3 aluminum oxide

Naphtha (petroleum), heavy alkylate 64741-65-7

1333-86-4 3.5 MGM3 carbon black

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Hq

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. No personal respiratory protective equipment normally required.

EYE PROTECTION: Safety glasses.

HAND PROTECTION: Protective gloves. Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

Not determined

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Not determined

Physical State Not determined

Odor Not determined

Odor threshold Not determined

Melting point / freezing point (°C) Not determined

Boiling point/range (°C) N.D. - N.D.

Flash Point, (°F / °C) Not determined

Evaporation rate Not determined

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive

limits

Vapour Pressure Not determined

Vapour density Not determined

Relative density Not determined

Solubility in / Miscibility with water Not determined

Partition coefficient: n-octanol/water Not determined

Auto-ignition temperature (°C) Not determined

Decomposition temperature (°C) Not determined

Viscosity Not determined

Not determined **Explosive properties**

Oxidising properties Not determined

9.2 Other information

VOC Content g/l:

VOC Content g/l:

Not determined

Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

Specific Gravity (g/cm3) 0.000

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

No Information

10.5 Incompatible materials

No Information

10.6 Hazardous decomposition products

No Information

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information Inhalation LC50: No information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 | Gas LC50 | Dust/Mist LC50 |
|-------------|--|----------------------------|-------------------------|------------------------|----------|-----------------------|
| 106264-79-3 | 6-methyl-2,4-bis(methylthio) phenylene-1,3-diamine | 1515 mg/kg (rat) | >2000 mg/kg (rabbit) | | 0.000 | 0.000 |
| 13463-67-7 | titanium dioxide | 10000 mg/kg, oral (rat) | | | 0.000 | 6,82 mg/l (rat) 4h |
| 27138-31-4 | dipropylene glycol dibenzoate | >2000 mg/kg Rat Dermal | | >200 mg/L Rat 4 h | 0.000 | 0.000 |
| 7631-86-9 | silicon dioxide (amorphous) | 3,160 mg/kg, rat | | 58.8 mg/l, 4hr, rat | 0.000 | 0.000 |
| 64741-65-7 | Naphtha (petroleum), heavy alkylate | 8000 mg/kg, oral, rat | 15,400 mg/kg, Rabbit | >3684 ppm 4 h, rat | 0.000 | 0.000 |
| 1333-86-4 | carbon black | >8000 mg/kg oral, rat | | | 0.000 | 0.000 |

Additional Information:

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form or progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other silicates as impurities, and above dei minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information
No information
No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB No information

assessment:

12.6 Other adverse effects: No information

| CAS-No. | Chemical Name | EC50 48hr | IC50 72hr | LC50 96hr |
|-------------|---|---|----------------|--------------------------|
| 1317-65-3 | limestone | No information | No information | |
| 106264-79-3 | 6-methyl-2,4-bis(methylthio)phenylene-1,3-diamine | 0.9 mg/L | No information | 7.3 mg/L (rainbow trout) |
| 13463-67-7 | titanium dioxide | >100 mg/l (EC50, 48h, Daphnia magna OECD202)ation | No information | >1000 mg/l |
| 27138-31-4 | dipropylene glycol dibenzoate | No information | No information | 3.7 mg/l |
| 1305-78-8 | calcium oxide | No information | No information | |
| 7631-86-9 | silicon dioxide (amorphous) | No information | No information | |
| 1344-28-1 | aluminum oxide | No information | No information | |
| 64741-65-7 | Naphtha (petroleum), heavy alkylate | No information | No information | |
| 1333-86-4 | carbon black | No information | No information | |

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number Not applicable

14.2 UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, n.o.s **Technical name** 6-METHYL-2,4-BIS(METHYLTHIO)PHENYLENE-1,3-DIAMINE

14.3 Transport hazard class(es)

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5 Environmental hazards Not applicable
14.6 Special precautions for user Not applicable
EmS-No.: Not applicable

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Germ cell mutagenicity

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

No SARA 313 substances exist in this product above de minimis concentrations.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category:

EPA VOC Content Limit (g/l):

Product VOC Content (g/l)

Not applicable

Not applicable

Thinning Recommendations: The coating is to be applied without thinning.

Application Recommendations: Not applicable

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical NameCAS-No.bis (2-ethylhexyl) terephthalate6422-86-2

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical NameCAS-No.bis (2-ethylhexyl) terephthalate6422-86-2

California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov

No Proposition 65 Reproductive Toxins exist in this product.

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

^{*} As per the federal EPA definition for coating categories in 40 CFR 59.401.

^{**} Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H340 May cause genetic defects.
H350 May cause cancer.

H351 Suspected of causing cancer.

H410 Very toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Reasons for revision

Changes have been made to Section 8 of the Safety Data Sheet (SDS). Please refer to the Exposure Controls / Personal Protection information in Section 8 of the SDS. This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million
mg/m3 Milligrams per cubic meter
TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter \leq 10 μm .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.