Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200



01/06/2023

1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 6323/POL Revision Date: 03/13/2024

Product Name: GS6 SILVER GRAY POLYOL

Base component of 2 components coating - Industrial use. Advised against: others than

Supersedes Date:

substance or mixture and uses recommended

advised against

Relevant identified uses of the

1.3 Details of the supplier of the safety data sheet

Manufacturer: Stonhard, Division of StonCor Group, Inc.

1000 East Park Avenue Maple Shade, NJ 08052

+1 856 7797500 (US)

Datasheet Produced by: ehs@stonhard.com

1.4 Emergency telephone number: +1 703-741-5970 - North America

+1 800-424-9300

+55 11 4349 1359 - South America +52 55 8526 4930 - Central America

+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, and Africa

+65 3163 8374 - Asia, South Asia, And Oceania

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 3
Hazardous to the aquatic environment, Chronic, category 3
Carcinogenicity, category 1B
Flammable Liquid, category 3
Germ Cell Mutagenicity, category 1B

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

2-methoxy-1-methylethyl-acetate, Pentane-2,4-dione, SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED

Flammable liquid and vapour.

H226

HAZARD STATEMENTS

Flammable Liquid, category 3

asting effects.
e use.
cautions have been read
es, sparks, open flames and ng.
ist/vapours/spray.
esh air and keep at rest in a 3.
edical advice/attention.
Geep container tightly
e :: :: : : : : : : : : : : : : : : : :

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

No information

3. Composition/Information On Ingredients

3.2 Mixtures

11	ingredients
Hazamonie	inarealente

Name According to EEC nepheline syenite	EINEC No. 609-369-8	CAS-No. 37244-96-5	<u>%</u> 10 - <25	Classifications	
titanium dioxide	236-675-5	13463-67-7	10 - <25	H351	Carc. 2
2-methoxy-1- methylethyl-acetate	203-603-9	108-65-6	2.5 - <10	H226-330	Acute Tox. 2 Inhalation, Flam. Liq. 3

closed.

Date Printed: 03/19/202	4				Product: 6323/POL
ethyl 3- ethoxypropionate	212-112-9	763-69-9	2.5 - <10	H226-335	Flam. Liq. 3, STOT SE 3 RTI
Zeolites	231-545-4	1318-02-1	1.0 - <2.5		
castor oil	232-293-8	8001-79-4	1.0 - <2.5		
hydrated, amorphous silica		112926-00-8	1.0 - <2.5		
Pentane-2,4-dione	204-634-0	123-54-6	1.0 - <2.5	H226-301-331	Acute Tox. 3 Inhalation, Acute Tox. 3 Oral, Flam. Liq. 3
1,3-benzenediol,4-[4,6-bis(2,4	604-910-4	153519-44-9	1.0 - <2.5	H410	Aquatic Chronic 1
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED	265-199-0	64742-95-6	0.1 - <1.0	H304-332-335-336-3 40-350	Acute Tox. 4 Inhalation, Asp. Tox. 1, Carc. 1B, Muta. 1B, STOT SE 3 NE, STOT SE 3 RTI

CAS-No.

37244-96-5 13463-67-7

108-65-6

763-69-9 1318-02-1

8001-79-4

112926-00-8

123-54-6

153519-44-9

64742-95-6

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: No Information

AFTER INHALATION: Move to fresh air. Keep respiratory tract clear.

M-Factors

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Harmful in contact with skin and if swallowed. May cause long-term adverse effects in the aquatic environment.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

Flammable.

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Water mist Dry powder Foam Carbon dioxide (CO2). High volume water jet. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions.

Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Electrical equipment should be protected to the appropriate standard. Use only in area provided with appropriate exhaust ventilation. Provide exhaust ventilation close to floor level. Wear personal protective equipment.

PROTECTION AND HYGIENE MEASURES: Keep working clothes separately. Keep away from food, drink and animal feedingstuffs. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice for diagnostics.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Keep in an area equipped with solvent resistant flooring. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

Name CAS-No. ACGIH TWA ACGIH STEL ACGIH Ceiling

nepheline syenite 37244-96-5 10. MG/M3

titanium dioxide	13463-67-7	10 MGM3 10 MGM3
2-methoxy-1-methylethyl-acetate	108-65-6	100 ppm
ethyl 3-ethoxypropionate	763-69-9	
Zeolites	1318-02-1	10.0 mg/m3
castor oil	8001-79-4	
hydrated, amorphous silica	112926-00-8	10.00 MG/M3
Pentane-2,4-dione	123-54-6	25 PPM
1,3-benzenediol,4-[4,6-bis(2,4	153519-44-9	
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED	64742-95-6	300.0 PPM

Name	CAS-No.	OSHA PEL	OSHA STEL
nepheline syenite	37244-96-5	5. MG/M3	
titanium dioxide	13463-67-7	15 MGM3	
2-methoxy-1-methylethyl-acetate	108-65-6		
ethyl 3-ethoxypropionate	763-69-9		
Zeolites	1318-02-1	0.8 mg/m3	
castor oil	8001-79-4		
hydrated, amorphous silica	112926-00-8	6.00 MG/M3	
Pentane-2,4-dione	123-54-6		
1,3-benzenediol,4-[4,6-bis(2,4	153519-44-9		
SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED	64742-95-6	500.0 PPM	

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with filter for organic vapor.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses. Safety goggles.

HAND PROTECTION: Solvent-resistant gloves. Follow the skin protection plan. Remove and wash contaminated clothing before re-use. Flame retardant antistatic protective clothing

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: SILVER RESIN

Physical State Liquid

Odor ESTER-LIKE ODOR

Odor thresholdNot determinedpHNon-aqueous

Melting point / freezing point (°C)

Not determined

Boiling point/range (°C) 80 - N.D.

Flash Point, (°F / °C) 113F / 45C

Evaporation rate Not determined
Flammability (solid, gas) Not determined

Upper/lower flammability or explosive N/A - N/A

limits

Vapour Pressure <1 mmHg

Vapour density Not determined Relative density Not determined

Solubility in / Miscibility with water Slight

Partition coefficient: n-octanol/water

Not determined

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity Thixotropic

Explosive properties Not determined

Oxidising properties

Not determined

9.2 Other information

VOC Content g/l: 234

Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

Specific Gravity (g/cm3) 1.369

10. Stability and Reactivity

10.1 Reactivity

Explosive reaction may occur on heating or burning.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat.

10.5 Incompatible materials

Do not store together with oxidizing and self-igniting products. Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information Inhalation LC50: No information

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
13463-67-7	titanium dioxide	10000 mg/kg, oral (rat)			0.000	6,82 mg/l (rat) 4h
108-65-6	2-methoxy-1-methylethyl-acetate	5155 mg/kg, oral (rat)	>5000 mg/kg (rabbit)	1105 mg/m3/4H	>100 ppm, rat, 4h	0.000
763-69-9	ethyl 3-ethoxypropionate	3200 mg/kg Rat, oral		>998 ppm 6 h rat	0.000	0.000
1318-02-1	Zeolites	3,160 mg/kg, rat		58.8 mg/l, 4hr, rat	0.000	0.000
8001-79-4	castor oil	5000 mg/kg, oral, rat			0.000	0.000
123-54-6	Pentane-2,4-dione	55 mg/kg oral, rat		10 mg/24 hours rabbit	0.000	0.000
64742-95-6	SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED	4610 mg/kg, oral, rat	>3480 mg/kg, rabbit	3670 ppm/4 hours, rat, inhalation	3670 ppm, rat, 4hrs	0.000

Additional Information:

This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

No information
No information
No information
No information
No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB No information

assessment:

12.6 Other adverse effects: No information

CAS-No.	<u>Chemical Name</u>	EC50 48hr	IC50 72hr	LC50 96hr
37244-96-5	nepheline syenite	No information	No information	
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
108-65-6	2-methoxy-1-methylethyl-acetate	No information	No information	161 mg/l (flathead minnow)
763-69-9	ethyl 3-ethoxypropionate	479.7 mg/l	No information	55.3 mg/l
1318-02-1	Zeolites	No information	No information	
8001-79-4	castor oil	No information	No information	
112926-00-8	hydrated, amorphous silica	No information	No information	
123-54-6	Pentane-2,4-dione	No information	No information	
153519-44-9	1,3-benzenediol,4-[4,6-bis(2,4	No information	No information	
64742-95-6	SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.; LOW BOILING POINT NAPHTHA - UNSPECIFIED	>1 - 10 mg/l	>1 - 10 mg/l	>10-100 mg/l

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. Dispose of as hazardous waste in compliance with local and national regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number UN1993

14.2 UN proper shipping name FLAMMABLE LIQUID, N.O.S.

Technical name (CONTAINS AROMATIC HYDROCARBONS, N-BUTYL ACETATE)

14.3 Transport hazard class(es) 3

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5Environmental hazardsNot applicable14.6Special precautions for userNot applicableEmS-No.:F-E, S-E

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Germ cell mutagenicity

Sara Section 313:

Benzene

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

Chemical NameCAS-No.%n-butyl acetate123-86-40.23

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

71-43-2

0

Chemical NameCAS-No.Pentane-2.4-dione123-54-6

U.S. Clean Air Act:

EPA Coating Category: Industrial Maintenance Coating

EPA VOC Content Limit (g/l): 450
Product VOC Content (g/l) 234

Thinning Recommendations: The coating is to be applied without thinning.

Application Recommendations: For professional use only.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> <u>CAS-No.</u>

polyester polyol 18275200000-5158

polyester polyol 67815-82-1

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u> <u>CAS-No.</u>

polyester polyol 18275200000-5158 polyester polyol 67815-82-1

California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov

WARNING: Reproductive Toxicant -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

^{*} As per the federal EPA definition for coating categories in 40 CFR 59.401.

^{**} Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

H330 Fatal if inhaled. H331 Toxic if inhaled. H332 Harmful if inhaled.

H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

H351 Suspected of causing cancer.

H410 Very toxic to aquatic life with long lasting effects.

Reasons for revision

Substance and/or Product Properties Changed in Section(s):

02 - Hazard Identification

03 - Composition/Information On Ingredients

09 - Physical and Chemical Properties

11 - Toxicological Information 15 - Regulatory Information Substance Chemical Name Changed Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million
mg/m3 Milligrams per cubic meter
TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration
IC50 Half maximal inhibitory concentration
PBT Persistent bioaccumulative toxic chemical
vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter \leq 10 μm .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.