# **Safety Data Sheet**

# Prepared In Accordance With HCS 29 C.F.R. 1910.1200



# 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier 23604/A Revision Date: 04/16/2025

Product Name: Stonseal PA7 Pewter Amine Supersedes Date: 02/21/2025

1.2 Relevant identified uses of the

substance or mixture and uses

advised against

Base component of 2 components coating - Industrial use. Advised against: others than

recommended

1.3 Details of the supplier of the safety data sheet

Manufacturer: Stonhard, Division of StonCor Group, Inc.

1000 East Park Avenue Maple Shade, NJ 08052

+1 856 7797500 (US)

Datasheet Produced by: ehs@stonhard.com

**1.4 Emergency telephone number:** +1 703-741-5970 - North America

+1 800-424-9300

+55 11 4349 1359 - South America +52 55 8526 4930 - Central America

+44 20 3885 0382 - Middle East, Eastern Europe, Western Europe, And Africa

+65 3163 8374 - Asia, South Asia, And Oceania

# 2. Hazard Identification

#### 2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 3 Carcinogenicity, category 2 Eye Irritation, category 2A Skin Sensitizer, category 1

## 2.2 Label elements

## Symbol(s) of Product



# Signal Word

Warning

## Named Chemicals on Label

titanium dioxide, tetraethyl n, n'-(methylenedicyclohexane-4,1,-diyl) bis-dl-aspartate

## **HAZARD STATEMENTS**

Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.		
Eye Irritation, category 2A	H319	Causes serious eye irritation.		
Carcinogenicity, category 2	H351	Suspected of causing cancer.		
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.		
PRECAUTION PHRASES				
	P201	Obtain special instructions before use.		
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.		
	P273	Avoid release to the environment.		
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.		
	P284	Wear respiratory protection.		
	P302+352	IF ON SKIN: Wash with plenty of soap and water.		
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.		
	P308+313	IF exposed or concerned: Get medical advice/attention.		
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.		
	P337+313	If eye irritation persists: Get medical advice/attention.		
	P362+364	Take off contaminated clothing and wash it before reuse.		
	P501	Dispose of contents and container in accordance with all		

## 2.3 Other hazards

No Information

# Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

# 3. Composition/Information On Ingredients

# 3.2 Mixtures

# Hazardous ingredients

Name According to EEC tetraethyl n, n'- (methylenedicyclohexan e-4,1,-diyl) bis-dl- aspartate	EINEC No. 429-270-1	<u>CAS-No.</u> 136210-30-5	<u>%</u> 25 - <50	<u>Classifications</u> H317-412	Aquatic Chronic 3, Skin Sens. 1
titanium dioxide	236-675-5	13463-67-7	2.5 - <10	H351	Carc. 2

local, regional, national and international regulations.

dipropylene glycol dimethyl ether	601-045-4	111109-77-4	2.5 - <10	H315-319	Eye Irrit. 2, Skin Irrit. 2
silicon dioxide (amorphous)	231-545-4	7631-86-9	1.0 - <2.5		
aluminum oxide		1344-28-1	1.0 - <2.5		
calcium oxide		1305-78-8	1.0 - <2.5	H315-318-335	Eye Dam. 1, Skin Irrit. 2, STOT SE 3 RTI
Bis(4-(1,2-bis (ethoxycarbonyl) ethylamino)-3- methylcyclohexyl) methane	412-060-9	136210-32-7	1.0 - <2.5		
2-Butenedioic acid (2E)-, 1,4-diethyl ester	210-819-7	623-91-6	1.0 - <2.5	H302-371	Acute Tox. 4 Oral, STOT SE 2
dipropylene glycol dibenzoate		27138-31-4	1.0 - <2.5	H412	Aquatic Chronic 3

Product: 23604/A

CAS-No.

carbon black

silica, crystalline free

M-Factors

601-216-3

136210-30-5 13463-67-7 111109-77-4 7631-86-9 1344-28-1 1305-78-8 136210-32-7 623-91-6 27138-31-4 112945-52-5 1333-86-4

Additional Information:

Date Printed: 04/16/2025

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

1.0 - < 2.5

0.1 - < 1.0

## 4. First-aid Measures

## 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

112945-52-5

1333-86-4

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

## Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

## 4.2 Most important symptoms and effects, both acute and delayed

Harmful if swallowed. Irritating to skin. May cause sensitization by inhalation. May cause sensitization by skin contact.

## 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

# 5. Fire-fighting Measures

#### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

## 5.2 Special hazards arising from the substance or mixture

No Information

#### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

## 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

# 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

# 7. Handling and Storage

#### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID: No Information** 

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

## 7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

# 8. Exposure Controls/Personal Protection

# 8.1 Control parameters

# Ingredients with Occupational Exposure Limits (US)

Name C	AS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
tetraethyl n, n'- (methylenedicyclohexane-4,1,-diyl) bis- dl-aspartate	136210-30-5			
titanium dioxide	13463-67-7	10 MGM3 2.5 MGM3 2.5 MGM3 0.2 MGM3 0.2 MGM3		
dipropylene glycol dimethyl ether	111109-77-4			
silicon dioxide (amorphous)	7631-86-9	10.0 mg/m3		
aluminum oxide	1344-28-1	1 mg/m3 (resp.fraction)		
calcium oxide	1305-78-8	2 MGM3		
Bis(4-(1,2-bis(ethoxycarbonyl) ethylamino)-3-methylcyclohexyl)methane	136210-32-7			
2-Butenedioic acid (2E)-, 1,4-diethyl ester	623-91-6			
dipropylene glycol dibenzoate	27138-31-4			
silica, crystalline free	112945-52-5	10. MG/M3		
carbon black	1333-86-4	3 MGM3		
<u>Name</u>	CAS-No.	OSHA PEL	OSHA STEL	
Name  tetraethyl n, n'- (methylenedicyclohexane-4,1,-diyl) bis- dl-aspartate	<u>CAS-No.</u> 136210-30-5	OSHA PEL	OSHA STEL	
tetraethyl n, n'- (methylenedicyclohexane-4,1,-diyl) bis-		OSHA PEL  15 MGM3	OSHA STEL	
tetraethyl n, n'- (methylenedicyclohexane-4,1,-diyl) bis- dl-aspartate	136210-30-5		OSHA STEL	
tetraethyl n, n'- (methylenedicyclohexane-4,1,-diyl) bis- dl-aspartate titanium dioxide	136210-30-5 13463-67-7		OSHA STEL	
tetraethyl n, n'- (methylenedicyclohexane-4,1,-diyl) bis- dl-aspartate titanium dioxide dipropylene glycol dimethyl ether	136210-30-5 13463-67-7 111109-77-4	15 MGM3 0.8 mg/m3	OSHA STEL	
tetraethyl n, n'- (methylenedicyclohexane-4,1,-diyl) bis- dl-aspartate titanium dioxide dipropylene glycol dimethyl ether silicon dioxide (amorphous)	136210-30-5 13463-67-7 111109-77-4 7631-86-9	15 MGM3 0.8 mg/m3 5 MGM3 5 MGM3 15	OSHA STEL	
tetraethyl n, n'- (methylenedicyclohexane-4,1,-diyl) bis- dl-aspartate titanium dioxide dipropylene glycol dimethyl ether silicon dioxide (amorphous) aluminum oxide	136210-30-5 13463-67-7 111109-77-4 7631-86-9 1344-28-1 1305-78-8 136210-32-7	15 MGM3 0.8 mg/m3 5 MGM3 5 MGM3 15 MGM3 15 MGM3	OSHA STEL	
tetraethyl n, n'- (methylenedicyclohexane-4,1,-diyl) bis- dl-aspartate titanium dioxide dipropylene glycol dimethyl ether silicon dioxide (amorphous) aluminum oxide calcium oxide Bis(4-(1,2-bis(ethoxycarbonyl)	136210-30-5 13463-67-7 111109-77-4 7631-86-9 1344-28-1 1305-78-8 136210-32-7	15 MGM3 0.8 mg/m3 5 MGM3 5 MGM3 15 MGM3 15 MGM3	OSHA STEL	
tetraethyl n, n'- (methylenedicyclohexane-4,1,-diyl) bis- dl-aspartate titanium dioxide dipropylene glycol dimethyl ether silicon dioxide (amorphous) aluminum oxide calcium oxide Bis(4-(1,2-bis(ethoxycarbonyl) ethylamino)-3-methylcyclohexyl)methane 2-Butenedioic acid (2E)-, 1,4-diethyl	136210-30-5 13463-67-7 1111109-77-4 7631-86-9 1344-28-1 1305-78-8 136210-32-7	15 MGM3 0.8 mg/m3 5 MGM3 5 MGM3 15 MGM3 15 MGM3	OSHA STEL	
tetraethyl n, n'- (methylenedicyclohexane-4,1,-diyl) bis- dl-aspartate titanium dioxide dipropylene glycol dimethyl ether silicon dioxide (amorphous) aluminum oxide  calcium oxide  Bis(4-(1,2-bis(ethoxycarbonyl) ethylamino)-3-methylcyclohexyl)methane 2-Butenedioic acid (2E)-, 1,4-diethyl ester	136210-30-5 13463-67-7 111109-77-4 7631-86-9 1344-28-1 1305-78-8 136210-32-7 623-91-6	15 MGM3 0.8 mg/m3 5 MGM3 5 MGM3 15 MGM3 15 MGM3	OSHA STEL	

**FURTHER INFORMATION:** Refer to the regulatory exposure limits for the workforce enforced in each country.

## 8.2 Exposure controls

**Personal Protection** 

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses.

Safety goggles.

**HAND PROTECTION:** Impervious gloves. **Body Protection:** Long sleeved clothing.

Remove and wash contaminated clothing before re-use. **OTHER PROTECTIVE EQUIPMENT:** No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined

areas.

# 9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Pewter resin

Physical State LIQUID

Odor Mild

Odor threshold

pH

Non-aqueous

Melting point / freezing point (°C)

Not determined

Not determined

Not determined

Not determined

Not determined

Flash Point, (°F / °C) >201F / >94C

Evaporation rate Not determined

Flammability (solid, gas) Not determined

Upper/lower flammability or explosive N/A - N/A

limits

Vapour PressureNot determinedVapour densityNot determinedRelative densityNot determined

Solubility in / Miscibility with water Negligible

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Not determined

Not determined

Viscosity 28770 CPS
Explosive properties Not determined

Oxidising properties

Not determined

9.2 Other information

VOC Content g/l:

Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

Specific Gravity (g/cm3) 1.304

# 10. Stability and Reactivity

# 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

## 10.2 Chemical stability

No decomposition if stored and applied as directed. Stable under normal conditions.

## 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

#### 10.4 Conditions to avoid

No Information

#### 10.5 Incompatible materials

Strong oxidizing agents. Acids and bases.

#### 10.6 Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

# 11. Toxicological Information

### 11.1 Information on toxicological effects

**Acute Toxicity:** 

Oral LD50: No information Inhalation LC50: No information

Irritation: No information available.

Corrosivity: No information available.

**Sensitization:** No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

**Mutagenicity:** No information available.

**Toxicity for reproduction:** No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	<u>Chemical Name</u>	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
136210-30-5	tetraethyl n, n'- (methylenedicyclohexane-4,1,- diyl) bis-dl-aspartate	>2000 mg/kg (rat)	>2000 mg/kg (rat)	>4224 mg/m3, 4 hr. (rat)	0.000	0.000
13463-67-7	titanium dioxide	10000 mg/kg, oral (rat)			0.000	6,82 mg/l (rat) 4h
7631-86-9	silicon dioxide (amorphous)	3,160 mg/kg, rat		58.8 mg/l, 4hr, rat	0.000	0.000

623-91-6	2-Butenedioic acid (2E)-, 1,4-diethyl ester	1780 mg/kg (rat)		0.000	0.000
27138-31-4	dipropylene glycol dibenzoate	>2000 mg/kg Rat Dermal	>200 mg/L Rat 4 h	0.000	0.000
112945-52-5	silica, crystalline free	10000 mg/kg, oral, rat		0.000	0.000
1333-86-4	carbon black	>8000 mg/kg oral, rat		0.000	0.000

#### Additional Information:

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form or progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group 1 carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Constituents may also include abestiform or non-asbestiform tremolite or other silicates as impurities, and above dei minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

# 12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

No information
No information
No information
No information
No information

12.2 Persistence and degradability: No information

**12.3 Bioaccumulative potential:** No information

**12.4 Mobility in soil:** No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

**12.6 Other adverse effects:** No information

CAS-No.	Chemical Name	EC50 48hr	IC50 72hr	LC50 96hr
136210-30-5	tetraethyl n, n'-(methylenedicyclohexane-4,1,-diyl) bis-dl-aspartate	88.6 mg/l	113 mg/l	66 mg/l (zebra fish)
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
111109-77-4	dipropylene glycol dimethyl ether	No information	No information	
7631-86-9	silicon dioxide (amorphous)	No information	No information	
1344-28-1	aluminum oxide	No information	No information	
1305-78-8	calcium oxide	No information	No information	
136210-32-7	Bis(4-(1,2-bis(ethoxycarbonyl)ethylamino)-3-methylcyclohexyl)methane	No information	No information	
623-91-6	2-Butenedioic acid (2E)-, 1,4-diethyl ester	No information	No information	
27138-31-4	dipropylene glycol dibenzoate	No information	No information	3.7 mg/l
112945-52-5	silica, crystalline free	No information	No information	

1333-86-4 carbon black No information No information

# 13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# 14. Transport Information

14.1 UN number N/A

**14.2 UN proper shipping name**Not regulated for transport

Technical name Not applicable

14.3 Transport hazard class(es) N/A

Subsidiary shipping hazard Not applicable

14.4 Packing group N/A

14.5 Environmental hazards
 14.6 Special precautions for user
 Not applicable
 Not applicable

EmS-No.: N/A

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

# 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

# U.S. Federal Regulations: As follows -

# **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Respiratory or Skin Sensitization, Serious eye damage or eye irritation

# Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

<u>Chemical Name</u> <u>CAS-No.</u> <u>%</u>

aluminum oxide 1344-28-1 2

## **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

Chemical NameCAS-No.dipropylene glycol dimethyl ether111109-77-4

#### U.S. Clean Air Act:

EPA Coating Category: Industrial Maintenance Coating

EPA VOC Content Limit (g/l): 450
Product VOC Content (g/l) 94

Thinning Recommendations: The coating is to be applied without thinning.

Application Recommendations: For professional use only.

# U.S. State Regulations: As follows -

## New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical NameCAS-No.bis (2-ethylhexyl) terephthalate6422-86-2

non-hazardous component 18275200000-5085 Secondary Amine 800963-52925

## Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical NameCAS-No.bis (2-ethylhexyl) terephthalate6422-86-2

non-hazardous component 18275200000-5085 Secondary Amine 800963-52925

# California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov

No Proposition 65 Reproductive Toxins exist in this product.

# International Regulations: As follows -

## \* Canadian DSL:

All chemical ingredients included on inventory or exempt.

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

<sup>\*</sup> As per the federal EPA definition for coating categories in 40 CFR 59.401.

<sup>\*\*</sup> Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

# Other Information

## Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H371	May cause damage to organs.
H412	Harmful to aquatic life with long lasting effects.

### Reasons for revision

Substance and/or Product Properties Changed in Section(s):
01 - Identification
Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes. This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Classification, Labeling & Packaging Regulation

## Acronym & Abbreviation Key:

CLP

ЕC European Commission European Union ΕU US United States Chemical Abstract Service CAS European Inventory of Existing Chemical Substances EINECS Registration, Evaluation, Authorization of Chemicals Regulation REACH Globally Harmonized System of Classification and Labeling of Chemicals GHS LTEL Long term exposure limit Short term exposure limit STEL Occupational exposure limit OEL ppm Parts per million Milligrams per cubic meter mg/m3 TLV Threshold Limit Value ACGIH American Conference of Governmental Industrial Hygienists OSHA Occupational Safety & Health Administration PEL Permissible Exposure Limits VOC Volatile organic compounds Grams per liter g/1

ng/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

Note P: The classification as a carcinogen or mutagen need not apply; the substance

contains less than 0,1 % w/w benzene

Note 10: The classification as a carcinogen by inhalation applies only to mixtures in

powder form containing 1 % or more of titanium dioxide which is in the form of

or incorporated in particles with aerodynamic diameter  $\leq$  10  $\mu m$ .

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.